

1002000100

ICX-500

Intelligentes Kommunikations-Gateway mit HD Voice

Nur für den Verkauf von maritimen und Energielösungen

Im Bereich Sicherheit und Schutz ersetzt der ICX-510-IA den ICX-500.

- Entwickelt, um kritische Kommunikation in jeder Umgebung zu ermöglichen
- Unterstützt 552 IP-Stationen
- Umweltfreundlich und energiesparend – max. 15 W
- Globale Vernetzung und Integration
- Duale Software-Images für Systemstabilität und geringe Ausfallzeiten bei Software-Upgrades
- Sicherer Start, Hardware-Root of Trust – RoT
- Hochwertige professionelle PA-Rundfunk- und Messaging-Dienste
- Sicherheitssprachführung für die öffentliche Sicherheit und Gebäudesicherheit
- 1 HE hoch, lüfterloses Design, vibrationsfest

UL Certified Intercom | ICX-AlphaCom | HD Voice

Beschreibung

Das intelligente Kommunikationsgateway ICX-500 verbindet Menschen, Geräte und Systeme mit einem beispiellosen Maß an Verwaltbarkeit, Skalierbarkeit, Robustheit und Interoperabilität.

ICX-500 erfüllt alle Kommunikationsanforderungen Ihres Standorts, da es sich leicht in Funktionalität und Systemgröße erweitern lässt und zukunftssicher konzipiert ist. Das System kann so angepasst werden, dass es Anwendungen nahezu unbegrenzter Spezifität und Komplexität unterstützt.

Zenitels ICX (Intelligent Communications X) ermöglicht den Einsatz von VoIP-Anwendungen, die in kritischen Situationen benötigt werden. ICX-500 bietet Systemverfügbarkeit auf Carrier-Niveau und schützt Ressourcen in einer IP-Umgebung durch eingebettete Sicherheitsmechanismen.

Die wichtigsten verwendeten Sicherheitsmechanismen sind Hardware-Root of Trust, Software-Integritätsprüfung (SHA256), eingeschränkter Verwaltungszugriff, separate Verwaltungsschnittstelle und interne Firewall.

Weitere Informationen zu ICX-500 finden Sie im Zenitel-Wiki .

Im Bereich Sicherheit und Schutz ersetzt ICX-510-IA ICX-500.


Technical Dimensions

www.zenitel.com info@zenitel.com Last revision date: 2026-08-04 15:35


Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.


SIDE VIEW




FRONT VIEW



REAR VIEW



TOP VIEW



All dimensions in mm

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Spezifikationen

MECHANISCH & UMWELT

Abmessungen (BxHxT)	162 x 44,5 x 200 mm / 6,38 x 1,75 x 7,87 Zoll
Gewicht	1 kg
Leistung	Nominal 24 – 48 VDC, 15 W (min./max.: 20 – 63 VDC)
Montage	Wandmontage oder 19-Zoll-Rack
Prozessorsubsystem	NXP LS1043
Speichersubsystem	Solid-State-Speicher (1048 MB Flash). MicroSD, USB
Temperaturbereich	-15°C bis +55°C
Relative Luftfeuchtigkeit	95 %

MERKMALE

Erinnerung	1048 MB SDRAM, 1048 MB NAND-Flash, 128 MB NOR-Flash
Teilnehmerkapazität	552 Sprechstellen pro Server
Anruf während der Stoßzeit	60.000 BHCA
IP-Telefone	552 IP-Telefone pro Server
Software-Integritätsprüfung	SHA256
IP-Priorität	DiffServ, IP-Nutzungsbedingungen
IP-Sicherheit	Hardware-Root of Trust, SSH, HTTPS, Firewall
SCHLUCK	RFC 3261, SIP-INFO, erneute Einladung. RFC 2833, RFC 4733,
Internes VoIP-Netzwerk	64 Kanäle
Externe VoIP-Netzwerke	64 Kanäle
ISDN-Trunk	ISDN PRI (30 Kanäle); VoIP externes Netzwerk + Gateway
Analoge Amtsleitung	FXO (4 und 8 Kanäle); VoIP-externes Netzwerk + Gateway
GSM-Trunk	Quadband-GSM; externes VoIP-Netzwerk + Gateway
Andere	Vingtor-Stentofon Data Scripting Engine (EDIO)
Konfiguration	AlphaPro über IP, Web
Überwachung und Protokollierung	SNMP-Trap, SNMP-MIB, Syslog, Web, E-Mail, SqLite
Software-Upgrade	Systemwiederherstellungs-Upgrade über SD-Karte, Web, automatisches Upgrade der IP-Station

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.


	Station.
VoIP-Audio	HD-Audio – 16 kHz (Hintergrundmusik, siehe zusätzliche Informationen im Zenitel-Wiki), HD-Sprache – G.722 (7 KHz), Telefon-Audio – G.711 (3,4 KHz)
Offene Duplex-Konferenz	Es können 20 offene Duplex-Konferenzen konfiguriert werden. An einer Konferenz können maximal 16 Teilnehmer teilnehmen, maximal 64 Teilnehmer können jedoch gleichzeitig auf mehrere Kanäle verteilt teilnehmen.
Push-to-Talk-Konferenz	50 Konferenzkanäle. Unbegrenzte Teilnehmerzahl. Prioritätsfunktionen
Gruppenanruf	250 Gruppen. Unbegrenzte Teilnehmerzahl. Prioritätsfunktionen
Anrufmodi	Offener Modus. Klingelmodus. Anrufanforderungsmodus. Prioritätsfunktionen
Audio-Nachrichten	PA-Übertragung. Automatische Vermittlung, Sprachführung (Türen, Aufzüge), Sicherheits-Sprachantwort
Einhaltung	CE, FCC Teil 15
Zertifizierungen	IEC/UL62368-1, EN61000-6-X, EN60945, EN 50121-4; Um den UL-Sicherheitsanforderungen zu entsprechen, muss das Gerät von einer Stromversorgung versorgt werden, die als Limited Power Source (LPS) oder PS2 (gemäß der Definition von IEC/UL 62368-1) oder als Stromversorgungsquelle der NEC-Klasse 2 spezifiziert ist

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

ZERTIFIZIERUNGEN	
EMV	IEC/EN 61000-6-2 Industrielle Störfestigkeit
	IEC/EN 61000-6-4 Industrieemissionen
	IEC/EN 61000-6-1 Störfestigkeit für leichte Industrieanwendungen
	IEC/EN 61000-6-3 Leichtindustrielle Emissionen
	EN 55032 Klasse B Multimediageräte
	IEC/EN 60533 Maritime
Seefahrt	IEC/EN 60945
Vibration	2 Hz – 100 Hz (IEC/EN 60068-2-6)
Trockene Hitze	55°C (IEC/EN 60068-2-2)
Niedrige Temperatur	-15°C (IEC/EN 60068-2-2)
Feuchte Hitze, zyklisch	40 °C / 93 % relative Luftfeuchtigkeit (IEC/EN 60068-2-2)
Sicherheit	UL62368-1-Zertifizierung
	CB-Zertifizierung nach IEC62368-1

Zubehör



IA-MB1

Montagehalterung für ICX-500/510

Artikelnummer 1002500020



IA-RS1

Rackregal für ICX-500/510 - 19

Artikelnummer 1002500010



IPS-AC1

PSU für ICX-500/510

Artikelnummer 1002510000



PROMAX-120-24

Power supply 100-240VAC/24VDC 5A

Artikelnummer 2990000041

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.



Power Supply 100-240VAC/48VDC 2A

Switched-mode power supply, 1-phase, 48 VDC output voltage, 2A current

Artikelnummer 2990000065

Used With



ICX-AlphaCom Core

Artikelnummer 1002600000



ICX-AlphaCom Lizenzen

Artikelnummer 100260xxxx



ILS-SC, IP-Station License, Softclient

IP Station License for SoftClient

Artikelnummer 1002600300



ILI-SIP2 / ILI-SIP4 / ILI-SIP8, SIP Trunking License 2, 4, 8 Lines

SIP Trunking License

Artikelnummer 100260210x

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.



ILI-REC(2-32), Active Recording Interface License

Active Recording Interface License

Artikelnummer 100260220x



ILI-API64 / ILI-API512, API License (64 and 512 Stations)

API License

Artikelnummer 100260230x



ILI-AN2 / ILI-AN8, AlphaNet License (2 Lines and 8 Lines)

AlphaNet License

Artikelnummer 100260200x



ILF-M-BAS / ILF-M-ENH / ILF-M-EXT (Audio Messaging Licenses, Basic and Enhanced)

Audio Messaging Licenses

Artikelnummer 1002604000/1002604100



ILS-IC, IP Station License

IP Station License

Artikelnummer 1002600100



ILS-SIP, SIP Station License

SIP Station License

Artikelnummer 1002600700



ILS-CRM

IP Station License for CRM

Artikelnummer 1002600200

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.