



1490005010

ITSV-5

HD IP Video Phone with 8" Screen

- 16 lines with up to 16 SIP accounts
- ⊗ 8" (1280×800) capacitive 10-point touch screen HD IPS LCD
- ❷ Built-in 2 mega-pixel CMOS tiltable camera with privacy shutter
- 12-way audio conferencing and 3-way 1080p 30fps video conferencing capability
- Dual-mic HD speakerphone with noise reduction, advanced echo cancellation, and excellent double-talk performance
- Seamless Integration Fully compatible with Zenitel Connect Pro, ICX-AlphaCom, IC-EDGE, and SIP-based systems.






Video Intercom SIP











HD Voice Video





Description

The ITSV-5 is a powerful IP video phone featuring Android 11, an 8" touch screen, real-time HD video telephony, built-in WiFi, Bluetooth, and more. The ITSV-5 delivers advanced SIP telephony features and out-of-the-box integration with our Zenitel Connect Pro, IC-EDGE and ICX-AlphaCom IP Intercom Platforms.

For more information go to Zenitel Wiki

Technical Dimensions





page 1/4

certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is

Specifications

GENERAL

| Graphic Display | 8" (1280x800) capacitive (10 points) touch screen IPS LCD |
|-----------------------------|--|
| Camera | Tiltable 2 mega-pixel CMOS camera with privacy shutter, 1080P@30fps |
| Auxiliary Ports | RJ9 headset jack (allowing EHS with Plantronics headsets), 3.5mm stereo headset with microphone, USB 3.0 port, Type-C, HDMI-out, HDMI-in |
| Feature keys | 2 function touch keys VOLUME +/-, 3 dedicated Android touch keys HOME, MENU, and BACK |
| Video Codec | H.263, H.264 BP/MP/HP |
| Video resolution | Up to 1080p |
| Video frame rate | Up to 30 fps |
| Operating temperature range | 0°C to +40°C |
| Storage temperature range | -10°C to +60°C |
| Relative humidity | 10% - 90% non-condensing |
| Power options | Power over Ethernet (PoE & PoE+) or power adapter. |
| Power over Ethernet | 802.3af Class 3, 802.3at Class 4 |
| Power adapter | Input: 100-240VAC 50-60Hz; Output 12VDC 1.5A |
| Network Interface | 2 x RJ45 (Ethernet) 10/100/1000 Mbps with integrated PoE/PoE+ |
| Bluetooth | Integrated, Bluetooth 5 + EDR |
| Wi-Fi | Integrated, dual-band 2.4 & 5GHz with 802.11 a/b/g/n/ac/ax, 2T2R, Wi- Fi Display & AirPlay |
| Security | User and administrator level passwords, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, TLS, SRTP, HTTPS, 802.1x media access control, Kensington Security Slot (Kensington Lock) support, anti-hacking secure boot |
| Protocols/Standards | SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, PPPoE, SSH, TFTP, NTP, STUN, SIMPLE, LLDPMED, LDAP, TR-069, 802.1x, TLS, SRTP, IPv6, OpenVPN®. |
| Audio technology | Wide-band Opus, wide-band G.722, G.711µ/a, G.729A/B, G.726-32, iLBC, in-band and out-ofband DTMF (In audio, RFC2833, SIP INFO), VAD, CNG, AEC, PLC, AJB, AGC, ANS, Noise Shield 2.0 |
| | English, German, Italian, French, |

page 2/4

www.zenitel.com info@zenitel.com

Last revision date: 2025-10-17 12:06

| Language support | Spanish, Portuguese, Russian, Croatian, Chinese, Korean, Japanese, Czech. |
|-------------------|--|
| Compliance | FCC: CFR 47 Part 15 Subpart B Class B; CFR 47 Part 15 Subpart C; CFR 47 Part 15 Subpart E; UL 60950-1 (power adapter); Part68 (HAC) CE: EN55032 Class B; EN55035;EN61000-3-2; EN61000- 3-3; EN62368-1; EN300328; EN301893; EN301489-1; EN301489-17; EN62311; RoHS RCM: AS/ACIF S040 AS/CA S004; AS/NZS CISPR 32; AS/NZS 62368.1; AS/NZS 4268 HDMI Source and Sink, HAC |
| Dimension (WxLxH) | 263 x 174 x 48 (WxLxH) mm |
| Weight | 1.08 kg |
| Warranty | 2 Years standard warranty, extendible up to total of 5 years (additional fee) |


Accessories



Wall Mount Bracket for ITSV-5

Used With





IP and SIP Video Intercom



TCIV-3+ | Video intercom

IP and SIP Video Intercom



TCIV-5+ | Video intercom

IP and SIP Video Intercom



TCIV-6+ | Video Intercom

IP and SIP Video Intercom



TKIV+ Video Intercom kit

Turbine Video - VoIP Intercom Module



TEIV-4+ | Video Intercom with RFID card reader space

IP & SIP Video Intercom with RFID card reader space



TEIV-1+ | Video Intercom with Keypad and Display

IP and SIP Video Intercom with Keypad and Display

page 4/4