zenitel

DATASHEET



3006100033

# CW-4T/VOF

Haut-parleur mural, 6 W avec contrôle du volume

## Description

- Haut-parleur mural avec transformateur pour applications dans centres commerciaux, hôtels, centres hospitaliers, etc.
- Contrôle du volume et fusible
- Parfaitement adapté aux systèmes de sonorisation, d'interphonie et à la diffusion de musique de fond
- Inclut un transformateur de ligne 100 V

Vissez le support de fixation au mur et fixez ensuite le haut-parleur sur le support à l'aide d'une vis.
Afin d'obtenir des performances optimales, utilisez systématiquement le bon voltage et ne dépassez pas les limites de fréquences indiquées.



www.zenitel.com info@zenitel.com

Last revision date: 2023-12-01 07:51

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

# Spécifications

## GÉNÉRAL

| | |
|---|---|
| Dimensions (LxHxP) | 250 x 170 x 88 mm |
| Poids | 1,2 kg |
| Montage | Vis, trous de fixation |
| Matériau / Couleur | Panneau de particules / Blanc ou beige |
| Températures de fonctionnement | De -40°C à +90°C |
| Connexions | Borne à ressorts |
| Alimentation nominale / maximale | 6 W / 8 W |
| Niveau de pression acoustique 1 W / 1 m | 90 dB |
| Puissance nominale du niveau de pression acoustique | 97 dB |
| Gamme de fréquence | 140 - 20000Hz |
| Directivité | (-6dB) 1kHz / 4kHz 140° / 80° |



www.zenitel.com info@zenitel.com Last revision date: 2023-12-01 07:51

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.