zenitel

DATASHEET

2310101038

SD429-PSGE1-X

Caméra dôme PTZ jour/nuit STT IP-66 avec zoom optique 29x



IP-66

Description

- Construction en acier inoxydable
- Mémoire intégrée
- Circuit UTP passif intégré
- 7 entrées d'alarme ; 2 sorties auxiliaires programmables
- Protection intégrée contre la foudre et les surtensions
- Compatible avec les système de dôme Spectra® IV SE 29X et 36X
- Caisson circulaire en acrylique
- Application sur plafond uniquement
- Conforme à la norme NEMA Type 4X
- Indice de Protection IP-66 contre la poussière et l'eau
- Utilisation en extérieur

www.zenitel.com info@zenitel.com

Last revision date: 2022-08-26 09:28

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

www.zenitel.com info@zenitel.com Last revision date: 2022-08-26 09:28

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Spécifications

GÉNÉRAL	
Dimensions (LxH)	Caméra 216,4 x 276,9 mm
Poids	4,5 kg

ÉLECTRIQUE	
Tension d'entrée	De 18 à 32 VAC; 24 VAC nominale
Alimentation	
24 VAC	73 VA nominale
24 VDC	3 VA nominale
Fusible	1,6 A

www.zenitel.com info@zenitel.com Last revision date: 2022-08-26 09:28

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.