1008080310

FCDC3

Convertisseur Ethernet Flowire - Tension CC



- Un câble à paire unique peut être utilisé pour distribuer l'électricité et le réseau de données
- Basculer entre l'activation et la désactivation de la transmission du PoE
- Les trajets de câble peuvent être plus longs, ce qui réduit le besoin de commutateurs et/ou de répéteurs
- Jusqu'à 9 appareils Flowire peuvent être connectés à la même structure de réseau à 2 fils
- L'infrastructure bifilaire existante peut être utilisée, ce qui réduit le coût total des projets de modernisation
- Le convertisseur Flowire peut être utilisé avec n'importe quel appareil compatible Ethernet

IP sur 2 fils

Description

Le convertisseur FCDC3 Flowire permet à Ethernet de fonctionner sur les deux mêmes fils que l'alimentation, offrant un câblage plus simple et s'ouvre pour des trajets de câbles plus longs. Le convertisseur Flowire est également capable d'alimenter des périphériques Ethernet qui y sont connectés, tels que des postes d'interphonie IP et des caméras de vidéosurveillance.

www.zenitel.com info@zenitel.com Last revision date: 2024-04-19 09:22

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Spécifications

MÉCANIQUE	
Dimension	107 x 74 x 26 mm
Poids	300g
Montage	Applique ou rail DIN
Indice de protection IP	IP-20

ENVIRONNEMENT	
Température de fonctionnement	-40°C à +70°C
Humidité supportée	De 15% à 95% (sans condensation)
Température de stockage	De -40°C à +70°C
Humidité de stockage	De 10% à 95% (sans condensation)

RÉSEAU	
Flowire	Jusqu'à 400 Mbps @ 100m *), Jusqu'à 200 Mbps @ 500m *), *) Testé dans des conditions typiques. La bande passante disponible dépend du type de câble, de la longueur du câble et du nombre d'appareils connectés. Longueur totale de câble pour un cluster Flowire ne doit pas dépasser 600 m.

ÉLECTRIQUE	**V NOM = 24 VDC – 48 VDC, V MIN = 18 VDC, V MAX = 56 VDC**
Tension nominale	NOM = 2,5 W, MAX = 6 W
Transfert de puissance, compatible avec PoE Mode B (paire de rechange)	P MAX = 15W

COMPATIBILITÉ ÉLECTROMAGNÉTIQUE (CEM)	
Immunité	IEC/EN 60945:2002/Cor1:2008, EN 61000-6-2:2005
Émissions	IEC/EN 60945:2002/Cor1:2008, EN 61000-6-3:2007+A1:2011

Accessoires

www.zenitel.com info@zenitel.com Last revision date: 2024-04-19 09:22

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.



Power supply 100-240VAC/24VDC 2A

Switched-mode power supply, 1-phase, 24 VDC output voltage, 2A current

Référence Produit: 2990000063



Power Supply 100-240VAC/48VDC 2A

Switched-mode power supply, 1-phase, 48 VDC output voltage, 2A current

Référence Produit: 2990000065



Power Supply 100-240VAC/24VDC 4A

Switched-mode power supply, 1-phase, 24 VDC output voltage, 4A current

Référence Produit: 2990000064



Power supply 100-240VAC/48VDC 5A

Switched-mode power supply, 1-phase, 48 VDC output voltage, 5A current

Référence Produit: 2990000066

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.