

3006200024

VSP-122P

Poste secondaire - Système de téléphone autogénérateur - 12 directions



Description

- ✓ Poste secondaire portatif
- ✓ 12 directions
- ✓ Boîtier waterproof
- ✓ Poignée de transport et câble de 5 mètres avec prise Amphenol 16 broches
- ✓ A utiliser avec le CD-16 sur le pont

Technical Dimensions



Spécifications

GÉNÉRAL

Connexions	Boîtier de raccordement CD-16
Boîtier	ROSE AISi12)
Combiné	RA-250 avec support
Couleur	Gris RAL7001 / Combiné noir
Indice de Protection IP	IP-66
Poids	2,6 kg
Dimensions (LxHxP)	220 x 220 x 185 mm (avec le combiné)

Accessoires



CD-16

Boîtier de raccordement



IRR-24

Relay Box



IRR-VSP-220

Relay box 220V AC for VSP-12 way



VSP-36-PEL-A

Headset with boom mic, headband, and 10m cable



VSP-36-PEL-A/20

Headset with boom mic, headband, and 20m cable



CD-4

Boîtier de raccordement waterproof



VSP-36-PELP-A

Headset with boom mic, headband, and 10m cable



VSP-36-PELP-A/20

Headset with boom mic, headband, and 20m cable



VSP-36-PELP-A/25

Headset with boom mic, headband,
and 25m cable