zenitel

DATASHEET

3006100028

CAR-4TF

Haut-parleur bi-directionnel mural, 4 W



Onboard communication

Description

- Haut-parleur bi-directionnel avec transformateur pour applications dans centres commerciaux, hôtels et centres hospitaliers
- Idéal pour les systèmes de sonorisation et la musique de fond
- À utiliser avec un amplificateur de ligne 100 V

Le haut-parleur CAR-4TF est un appareil destiné à une utilisation générale à utiliser avec sur des lignes de 50/100 V. Ce haut-parleur diffuse de l'audio des deux côtés, ce qui le rend parfaitement adapté à une utilisation dans des espaces publics où les messages audio doivent être répartis uniformément.

www.zenitel.com info@zenitel.com

Last revision date: 2024-05-21 08:58

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

www.zenitel.com info@zenitel.com Last revision date: 2024-05-21 08:58

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Spécifications

GÉNÉRAL

Matériau / Couleur	Aluminium / Anodisé
Dimensions (ØxP)	152 x 90 mm
Montage	Support de fixation avec pied
Connecteur	Câble de 1 m
Poids	1,5 kg
Alimentation nominale / maximale	4W / 6W
Niveau de pression acoustique 1 W / 1 m	90 dB
Puissance nominale du niveau de pression acoustique	96 dB
Gamme de fréquence	150-16000 Hz
Directivité (-6dB) 1kHz / 4kHz	360° / 50°
Indice de Protection IP	IP-30

www.zenitel.com info@zenitel.com Last revision date: 2024-05-21 08:58

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.