zenitel

DATASHEET

1009104000

ATLB-12

Carte de ligne abonné



Description

- Carte de grande capacité pour téléphones analogiques supportant 12 lignes abonnés
- Supporte toutes les fonctionnalités des téléphones ACM
- Supporte les télécommunications et la numérotation DTMF
- Chaque carte comporte 6 sorties de commande à distance programmables
- Comprend des circuits de commutation vocale pour deux conversations interphoniques
- Connexion et déconnexion de la carte à chaud

La carte ATLB-12 est une carte analogique de grande capacité permettant le raccordement de 12 lignes d' abonnés offrant l'accès à toutes les fonctionnalités des téléphones ACM Vingtor-Stentofon.

www.zenitel.com info@zenitel.com

Last revision date: 2022-08-26 09:27

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Cette carte est supportée par :

- Les systèmes téléphoniques ACM
- Les systèmes standard intégrés ACM
- Les systèmes avancés intégrés ACM

La fonction « hot-line » est disponible pour connecter des téléphones qui ne comportent pas de touches de numérotation. Un numéro préprogrammé est alors composé dès que vous décrochez le combiné. Le numéro préprogrammé peut vous permettre de joindre un autre poste ou d'activer une fonction dans le serveur.

La carte ATLB-12 dispose de 6 sorties de commande à distance contrôlées par logiciel pour connecter des équipements externes comme des gyrophares, des signaux de contrôle de sonorisation et bien plus encore.

La carte s'enfiche dans les positions 1 à 6 du serveur ACM E7 et dans les positions 1 à 23 des serveurs ACM E20 et ACM E26.

Avec les serverus E20 et E26, la carte peut être insérée ou remplacée sans avoir besoin de couper l'alimentation du système grâce à la fonction de connexion de la carte à chaud.

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Spécifications

GÉNÉRAL

Type d'interface	FXS
Signalisation	DTMF
Résistance de boucle FXS	600 Ohm
Tension à combiné-raccroché	-42 V
Tension de sonnerie	50 Vrms
Fréquence de sonnerie	25 Hz
Gamme de fréquence	300 - 3400 Hz
Diaphonie à 1 kHz	< -75 dB
Ratio S/N (conversation)	45 dB
Capacité	12 lignes abonnés, jusqu'à 3 téléphones par ligne
Scanner Duplex	2
Sorties de commande à distance	6
Câblage	Câble blindé, 1 paire torsadée 0,5 mm2
Distorsion	< 2%
Tension de ligne	-48 V

www.zenitel.com info@zenitel.com Last revision date: 2022-08-26 09:27

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.