

3006102036

EHS-220O

Gyrophare orange 220 VAC



Description

- ✓ À utiliser dans les espaces bruyants pour notifier un appel
- ✓ Peut être utilisé avec tous les systèmes Vingtor-Stentofon
- ✓ À utiliser avec une unité de relais

Spécifications

GÉNÉRAL

| | |
|--------------------------------|--|
| Alimentation | 220 VAC +- 10% 50-60 Hz |
| Source lumineuse | 40 W Ba-15d |
| Courant nominal | 200mA |
| Fréquence de clignotement | 180 tours par minute (rpm) |
| Températures de fonctionnement | De -10°C à +50°C |
| Matériaux | Socle : acier doux peint / Lentille : PC |
| Couleur du socle | Gris |
| Rapport cyclique | 100% |
| Connexion | Câble de 1 m |
| Indice de Protection IP | IP-54 |
| Dimensions (ØxH) | 148 x 215 mm |
| Poids | 1,1 kg |
| Températures de stockage | De -10°C à +55°C |
| Humidité supportée | <95% (sans condensation) |

RÉFÉRENCE

DESCRIPTION

| | |
|------------|---|
| 3006102033 | EHS-220B Gyrophare 220 VAC Bleu |
| 3006102034 | EHS-220G Gyrophare 220 VAC Vert |
| 3006102035 | EHS-220K Gyrophare 220 VAC Transparent |
| 3006102037 | EHS-220R Gyrophare 220 VAC Rouge |

GÉNÉRAL

Dimensions (ØxH) 147 x 220 mm

Poids 0,9 kg

page 3/3

www.zenitel.com

info@zenitel.com

Last revision date: 2025-11-10 15:15

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend: Zenitel – All rights reserved.