zenitel

DATASHEET

3005020009

CU-100

Unité centrale pour CTB-10



Description

- Unité centrale 10 lignes pour le système CTB-100V
- Fonctionne avec les panneaux CTB-20 et CTB-20 W/V01
- AUX / entrée d'alarme
- Sortie pour le système de sonorisation
- Alimentation 24 VDC
- Sortie de ligne 100 V
- Puissante amplification lorsque vous l'utilisez avec un amplificateur de puissance 100 V

www.zenitel.com info@zenitel.com

Last revision date: 2023-09-11 19:56

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Spécifications

www.zenitel.com info@zenitel.com Last revision date: 2023-09-11 19:56

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

GÉNÉRAL

Matériau / Finitions	Aluminium / Noir
Montage	Sur cloison avec des vis 4 x 4 mm
Terminaux	Borniers à vis enfichables pour câble de max. 2,5 mm²
Fusibles	F1, F2, F3, F4, 1 A 5 x 20
Switch DIP	Pour les zones de sonorisation, régler les priorités, régler la réception des appels
Potentiomètre	Pour l'ajustement du volume de la ligne 1-5, 6-10
Dimensions (LxHxP)	400 x 400 x 120 mm
Poids	Environ 3,2 kg
Connexions	4 panneaux d'opération, jusqu'à 10 postes secondaires, AUX, sonorisation
Entrée AUX	0 dB 0,775 V / 600 Ohm
Contact d'alarme	Contact sec à fermeture
Gamme de fréquence	200 Hz - 8 KHz (-3 dB)
Températures de fonctionnement	De -20°C à +55°C
Alimentation	20 - 32 VDC
Consommation de puissance à 24 VDC	2,5 A
Puissance de sortie	30 W par 10 lignes
Impédance de sortie	20 Ohm par ligne
Indice de Protection IP	IP-20

www.zenitel.com info@zenitel.com Last revision date: 2023-09-11 19:56

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.