

1200100121

VIPEDIA-12-PRO

Routeur audio PAVA avec carte réseau - compatible Dante



- Connectivité IP
- DANTE®
- Traitement audio professionnel de haute qualité
- Traitement audio 24 BIT 48 kHz
- 12 Entrées et sorties audio analogiques
- 6 Entrées audio IP
- Entrées et sorties à usage cénéral
- OPTIONS DE CONTRÔLE FLEXIBLES
- Compatible avec la gamme d'amplificateurs











Dante



Civil Defence Approval



Certification EN54-16

Description

ASL's VIPEDIA-12-PRO audio router provides 24 channels of high-quality digital signal processing (12 inputs and 12 outputs), IP networking and Dante connectivity. Along with comprehensive control all in a single costeffective 19" rack mount enclosure.

Using Digital Backbone (DBB), up to four VIPEDIA routers can be locally linked within a single cabinet. Providing a powerful 48×48 way simultaneous routing matrix with sub millisecond latency. Using the IP network, up to thirty-two VIPEDIA can be distrusted around a site. The VIPEDIA integrates seamlessly with ASL's V400, X400 and V2000 amplifier ranges to provide a full EN 54 compliant PAVA system. This includes the monitoring and control of up to 64x (V400 / X400) or 32x (V2000) amplifier mainframes and their associated amplifier modules.

Accessoires

page 1/2

BMB01 from datasheet

BMB01

Extension GPIO RS485 sur rail DIN



NETWORK-SWITCH-LP01

PAVA Network Switch - Layer 2



VIPEDIA-BOA01

Din Rail Mount RJ45 Breakout Adapter - Single Port



VIPEDIA-BOA02

Din Rail Mount RJ45 Breakout Adapter - Four Port

Used With



V2000

Rack amplificateur de puissance PAVA 2000W (sans amplificateur installé)

page 2/2