



1008123020

TFIX-2

Ex IP Intercom Station

This product has been replaced by [TFIX-2-V2](#)



Turbine



IP66



IEC Ex Intercom



Atex



Active Noise Cancelling



IP over 2-wire

Description

- ✓ Ex IP intercom for potentially explosive atmospheres - Directive 2014/34/EU
- ✓ Ethernet compatible 2-wire interface
- ✓ DIP functionality for use with AlphaCom audio servers
- ✓ SIP/VoIP functionality for use with 3rd-party systems
- ✓ Dust- and water-protected to IP66
- ✓ Monitoring and self-diagnostics of critical functionality


The TFIX-2 Explosion-proof intercom station is a rugged device, designed for harsh environments and meets industrial and offshore requirements as well as requirements for ATEX Zone 1 operation. The plastic housing is designed to withstand most chemical and environmental hazards found on- or offshore.

The TFIX-2 features 6 programmable buttons.

The intercom station is fully digital and offers crystal clear audio with high output through an internal amplifier and 78 mm speaker, delivering over 90 dB SPL. Active Noise Reduction and Acoustic Echo Cancelling allows for hands-free two-way communication with superior audio quality.

Intercom status indicators display the status of the system and are compatible with AlphaCom and Exigo systems as well as SIP functionality for use with 3rd party systems.

Technical Dimensions



Specifications

MECHANICAL

Dimensions	345 x 178 x 101 mm
Weight	4 kg
Mounting	On-wall box (included)
Color	Black

ENVIRONMENTAL

Operating temperature	-20°C to +60°C
Storage temperature	-40°C to +70°C
Operating humidity	10% to 95% RH (non-condensing)
Storage humidity	10% to 95% RH (non-condensing)
Air pressure	600 hPa to 1200 hPa
IP-rating	IP64 in accordance with IEC 60079-0
	IP66 in accordance with EN 60945
IK rating	7J for enclosure
	4J for cable glands

ELECTRICAL

PoE	NO, proprietary 2-wire data- and powerbus
Power consumption	4.2 W (idle) to 8 W (max)
DC power	24 VDC

NETWORK

Connection	2 x 2-wire
Connection type	Screw terminals
Functions	Auto negotiating
Built-in switch	N/A
Compatibility	SIP, ICX-AlphaCom, IC-EDGE, G.711, G.722, G.729, HD Voice

INPUTS AND OUTPUTS

Handheld Microphone	Microphone (bal), PTT
Handset	Microphone (bal), Speaker (bal) + PTT
Headset	Microphone (bal), Speaker (bal), + PTT
Digital inputs/outputs	NO
Relay outputs	NO
Audio	Yes, for audio accessories
Aux power	Provided by network cable

CERTIFICATIONS

Immunity	EN 60945, EN 61000-6-2
Emission	EN 60945, EN 61000-6-3, EN 61000-6-4
CENELEC safety standards	EN 60079-0: 2012, EN 60079-7: 2007, EN 60079-11: 2012, EN 60079-18: 2009
IEC safety standards	IEC 60079-0: 2011, IEC 60079-7: 2006-07, IEC 60079-11: 2011, IEC 60079-18: 2009
Marking	II 2(2) G Ex e ib mb [ib] IIC T4 Gb -20°C ≤ Ta ≤ +60°C

Accessories



TAX-2B

Ex-Approved Plugbox & Cable for Headset with PTT



TAX-3

EX Handset



EMMAX-1H

Handheld Industrial EX Microphone For Exigo/Turbine



FCDC2

Flowire Ethernet Converter - non-PoE This product has been replaced by 1008080310 FCDC3 Flowire Ethernet Converter



Power Supply 100- 240VAC/24VDC 4A

Switched-mode power supply, 1-phase, 24 VDC output voltage, 4A current