

2340010001

DSP-15EExmN

EX Speaker 15 W



---

---

## Description

- ✓ Rated /max. power 15W
- ✓ Material: Antistatic PA / Black

Bracket and all outside nuts and screws in stainless steel

When mounting the loudspeaker please ensure that it is re-assembled in the same manner in which it was received. Fasten bracket with 1-3 screws. To change the position of the loudspeaker, please adjust the standard U-bracket (by loosening / tightening the screws) as required.

For optimum performance, always use the correct voltage / power and operate within the frequency limits as stated. Use only certified/specified cable glands and blanking plugs. Do not open loudspeaker when energized. Fasten lid with a torque of 2 - 3 Nm

# Specifications

<b>SPECIFICATIONS</b>	<b>IIB</b>
Material/colour	Antistatic PA/Black
Mounting	Bracket
Termination	e-chamber, push terminals
Weight	2,2 kg
IP rating	66/67
Max./min.amb.temp	50°C / -50°C
Impedance / max. power	20 Ω / 30 W
SPL 1W/1m	105 db
SPL Rated Power	118 db
Effective freq. Range	380 - 7000 Hz
Dispersion (-6dB) 1kHz / 4kHz	200° / 50°
Directivity factor, Q	1,8
Options	Impedance, colors, label