

2211020106

## KWS8000

DECT Rack including power supply, cable and software license



---

---

## Description

The DECT Server 8000 is a modular, scalable and flexible wireless mobility solution with combined analog and SIP VoIP interface that can be customized to exactly match your wireless telephony needs today and in the future. With its ability to easily scale, it fits the needs of medium to large-sized enterprise businesses.

- ✓ Analog system, Power, data and synchronization for base stations on only 2 wires
- ✓ Up to 30 users with no extra license (upto 4095 users with extra license)
- ✓ SIP (G711u law) 32 simultaneous calls or Analog (8 or 16 lines cards) integration to PABX
- ✓ Supports messaging with an alarm server
- ✓ 9-card slots (1 dedicated for processor card, up to 8 interface cards - No card included)
- ✓ A base station card can connect to up to eight DECT base stations.
- ✓ Can also connect up to 1024 IP DECT base stations
- ✓ 110-240 VAC External power - Included
- ✓ 1 year Software License for 30 users - Included

Note: 2211020106 includes item 2211020144 (IP DECT Server KWS8000) and 2211020140 (Software Assurance License for 1 year)

# Specifications

## GENERAL

Size (WxHxD)	177 x 422 x 328 mm
Weight	5,34 kg

## ACCESSORIES

3006230037	Spare Power supply for DECT server KWS8000
2211020103	Analog Interface Card 16 lines
2211020104	Analog Interface Card 8 lines
2211020108	CPU Card for KWS without link option
2211020111	Termination connector for KWS8000
2211020110	Wall hanger for KWS8000

## Accessories



### KWS-AIC16

Analog Interface Card 16 lines



### KWS-AIC8

Analog Interface Card 8 lines



### KWS-CPU

CPU Card for KWS without link option



### KWS-CPUL

CPU Card for KWS with link option

## Used With



### DECT Base Station

Base station 4ch for KWS2500  
and KWS8000