zenitel

DATASHEET

3005010102

SPA-AL-REL-V2

3 x Potential free relay output



Description

- GA-steady
- GA-pulsing
- GA-pulsing with mute
- Contact set rated at 230 VAC or 24 VDC
- Optional rack unit

www.zenitel.com info@zenitel.com

Last revision date: 2023-07-17 21:19

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

GENERAL

Dimension (WxH)	124 x 65.5 mm
Mounting	Rack mount internal
Weight	0.5 Kg
Operating temperature	-15°C to +55°C

www.zenitel.com info@zenitel.com Last revision date: 2023-07-17 21:19

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.