

3006102032

EHS-1100

Rotary light 110 VAC

Description

- Used in noisy areas to indicate a call
- Can be used with all Industrial Stations or Telephones
- Must use CRB-7 when used on Industrial Telephones
- Equipped with 1m Cable

Rotating beacon in painted mild steel housing, for less aggressive environments. Enduring with low noise friction-gear.

Specifications

GENERAL

Size (ØxH)	148Ø x 215H
Weight	1.1 kg
Nominal Voltage	115 VAC (50-60 Hz) +/- 10%
Flash freqency	180 r.p.m.
Current Consumption	400 mA (current at nominal voltage)
Lamp source	BA15d 40W
Ingress Protection	IP-54
Housing Colour	Grey
Housing Material	Mild Steel (Painted Grey)
Lens material	PC
Operating temp.	-10 to +50 °C
Connection	Flying leads
Environmental Condition	Protected

ORDER NUMBER	DESCRIPTION
2340200001	EHS-110B Rotary Light 110VAC Blue
2340200002	EHS-110G Rotary Light 110VAC Green
2340200003	EHS-110K Rotary Light 110VAC Clear
2340200004	EHS-110R Rotary Light 110VAC Red
3006102032	EHS-110O Rotary Light 110VAC Orange

page 2/3

ACCESSORIES

3006204182	Spare Lens for EHS, Red
3006204181	Spare Lens for EHS, Clear
3006102053	Spare Lens for EHS, Green
3006102052	Spare Lens for EHS, Orange
3006102051	Spare Lens for EHS, Blue

page 3/3