

1007082000

Industrial Master Station

Noise Cancelling



Description

- ✓ Fully equipped master station with free access to all extensions and features
- ✓ Rugged waterproof and chip-resistant casing in orange makrolon
- ✓ Noise cancelling microphone with protective flange
- ✓ Red microphone live lamp
- ✓ Built-in 10W (8 Ohm) VOX operated power amplifier
- ✓ For use with external loudspeaker with or without power amplifier
- ✓ Screw terminals for easy connection of installation cables

This industrial master station is a waterproof model designed for humid, dirty and outdoor conditions. The station consists of a rugged splashproof and chip-resistant casing of orange makrolon and has a folio keyboard on the front. The front panel is hinged to the back casing to allow easy access during installation and service. The station has screw terminals with labels for easy installation. Two glands ensure waterproof and dustproof connection of


page 1/6

installation cable and loudspeaker wires.

The unit is equipped with a noise cancelling microphone preventing background noise from disturbing the conversation. A 20-70 Ohm external loudspeaker connects to the station or, alternatively, connect an 8-20 Ohm speaker for use with the built-in 10W (8 Ohm) VOX operated power amplifier. The external speaker must be placed at least one meter away from the station. The power amplifier requires separate 12V AC / 2 Amp power supply. The loudspeaker volume is adjustable with potentiometers located inside the casing and the station is programmable for permanent private mode by strap-plug setting inside the station.

The station is prepared for connection of a separate external handset.

Technical Dimensions



Specifications

MECHANICAL

Operating Voltage	From exchange without power amp. 12 VAC / 2 Amp with power amp.
Cable Requirements	2 pair 0.5 mm ² / 24 AWG twisted telephone cable. + 1 pair 0.8 mm ² / 20 AWG (to transformer if power amplifier is used)
Temperature	-50°C to +55°C
Relative humidity	0% - 95%
Dimensions: (W x H x D)	160 x 240 x 137 mm, 6.24" x 9.36" x 5.34"
Finish	Orange makrolon
Orange makrolon	1.5 W (20 Ohm), 10W (8 Ohm) with power amplifier
Max. Loudspeaker Output	20-70 Ohm without power amplifier, 8-20 Ohm with power amplifier

page 3/6

ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
1007082000	Noise Cancelling Industrial Master Station (external speaker is required)	1.1 kg / 2 lb. 7 oz
Accesories:		
VML-1520	Horn Loudspeaker, 15 W/20 Ohm, IP-66	1.4 kg/3 lb
VMP-211	Wall Mount Handset Unit (with PTT key), IP- 44	0.9 kg/2 lb
VMP-250	Wall Mount Handset Unit /with PTT key), IP- 65	0.9 kg/2 lb
EOTRF 10115	220 VAC/12 VAC Mains Transformer (for power amplifier option)	1.4 kg/3 lb

GENERAL

Frequency Range	500-5000 Hz (\pm 8 dB)
Mic. Impedance for external handset	200 - 600 Ohm
Connector Type	Screw terminals
Gland Diameter	2 x PG9
Indicator	LED (red)

Accessories



VMP-36-PEL

Headset with Boom Microphone and 10 Meter Cable



VMP-36-PELP

Headset with Boom Microphone, 10 Meter Cable and Plug



CD-7-VMP

Plugbox Waterproof for VMP-36-PELP



VMP-211

Wall Mounted Handset



VMP-250

Wall Mounted Handset Waterproof



VML-1520

Horn Loudspeaker 15W, 20 OHM Waterproof



EHS-24O – Rotary Signal Light, 24 V DC (Orange)

Rotary Light 24V DC



EHS-220O – Rotary Signal Light, 220 V AC (Orange)

Rotary Light 220VAC



Model-A

Telephone Booth



IRR-3

Relay Box

page 6/6

www.zenitel.com

info@zenitel.com

Last revision date: 2024-09-02 11:03

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend: Zenitel – All rights reserved.