zenitel

DATASHEET

2310101038

# SD429-PSGE1-X

Camera dome SST day-night PTZ 29x optical zoom IP66



IP66

## Description

This item has been replaced by item number 2310101057

- All Stainless Steel Construction
- Built-in Back Box Memory
- Intregrated Passive UTP Circuit
- 7 Alarm Inputs; 2 Programmable Auxiliary Outputs
- Built-in Surge and Limited Lightning Protection
- Compatible with 29X and 36X Spectra® IV SE Dome Drives
- Bubble Constructed of Optically Clear Acrylic
- Environmental Pendant Model Only
- Meets NEMA Type 4X and IP66 Standards



www.zenitel.com info@zenitel.com

Last revision date: 2022-08-26 09:28

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

- Outdoor Applications



www.zenitel.com info@zenitel.com Last revision date: 2022-08-26 09:28

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

# Specifications

| GENERAL | |
|---|---|
| Size (WxH) | Camera 216,4 x 276,9 mm |
| Weight | 4,5 kg |

| ELECTRICAL | |
|---|---|
| Input Voltage | 18 to 32 VAC; 24 VAC nominal |
| Input Power | |
| 24 VAC | 73 VA nominal |
| 24 VDC | 3 VA nominal |
| Fuse | 1.6A |



www.zenitel.com info@zenitel.com Last revision date: 2022-08-26 09:28

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.