

1008123040

## TFIX-4

Ex IP Telephone

This product has been replaced by [TFIX-T-V2](#)



Turbine



IP66



Atex



Active Noise Cancelling



IP over 2-wire

## Description

- ✓ Ex IP telephone for potentially explosive atmospheres - Directive 2014/34/EU
- ✓ Ethernet compatible 2-wire interface
- ✓ DIP functionality for use with AlphaCom audio servers
- ✓ SIP/VoIP functionality for use with 3rd-party systems
- ✓ Dust- and water-protected to IP66
- ✓ Monitoring and self-diagnostics of critical functionality
- ✓ Visible status indicators on front panel

The TFIX-4 Explosion-proof telephone is a rugged device, designed for harsh environments and meets industrial


and offshore requirements as well as requirements for ATEX Zone 1 operation. The plastic housing is designed to withstand most chemical and environmental hazards found on- or off-shore.

The TFIX-4 features a full keypad with 1 programmable button and keys for manual override (PTT) and Cancel.

The telephone is fully digital and offers crystal clear audio. Active Noise Reduction allows for two-way communication with superior audio quality.

Status indicators display the status of the system and are compatible with AlphaCom and Exigo systems as well as SIP functionality for use with 3rd party systems

## Technical Dimensions



# Specifications

## MECHANICAL

Dimensions	345 x 178 x 101 mm
Weight	4 kg
Mounting	On-wall box (included)
Color	Black

## ENVIRONMENTAL

Operating temperature	-20°C to +60°C
Storage temperature	-40°C to +70°C
Operating humidity	10% to 95% RH (non-condensing)
Storage humidity	10% to 95% RH (non-condensing)
Air pressure	600 hPa to 1200 hPa
IP rating	IP64 in accordance with IEC 60079-0
	IP66 in accordance with EN 60945
IK rating	7J for enclosure
	4J for cable glands

## ELECTRICAL

PoE	NO, proprietary 2-wire data- and power bus
Power consumption	4.2 W (idle) to 8 W (max)
DC power	24 VDC

## NETWORK

Connection	2 x 2-wire
Connection type	Screw terminals
Functions	Auto negotiating
Built-in switch	N/A
Compatibility	SIP, ICX-AlphaCom, IC-EDGE, G.711, G.722, G.729, HD Voice

## INPUTS AND OUTPUTS

Handheld Microphone	Microphone (bal), PTT
Handset	Microphone (bal), Speaker (bal) + PTT
Handset	Microphone (bal), Speaker (bal) + PTT
Digital inputs/outputs	No
Relay outputs	No
Audio	Yes, for audio accessories
Aux power	Provided by network cable

## CERTIFICATIONS

Immunity	EN 60945, EN 61000-6-2
Emission	EN 60945, EN 61000-6-3, EN 61000-6-4
CENELEC safety standards	EN 60079-0: 2012, EN 60079-7: 2007, EN 60079-11: 2012, EN 60079-18: 2009
IEC safety standards	IEC 60079-0: 2011, IEC 60079-7: 2006-07, IEC 60079-11: 2011, IEC 60079-18: 2009
Marking	II 2(2) G Ex e ib mb [ib] IIC T4 Gb -20°C ≤ Ta ≤ +60°C

## Accessories



### EMMAX-1H

Handheld Industrial EX Microphone For Exigo/Turbine

Item Number: 1023533511



### TAX-2B

Ex-Approved Plugbox & Cable for Headset with PTT

Item Number: 1008150025



### TAX-3

EX Handset

Item Number: 1008150030



### FCDC2

Flowire Ethernet Converter - non-PoE This product has been replaced by 1008080310 FCDC3 Flowire Ethernet Converter


Item Number: 1008080210



Power Supply 100-  
240VAC/24VDC 4A

Switched-mode power supply, 1-phase, 24 VDC output voltage, 4A current

Item Number: 2990000064



EGA-1

Button Protection Covers

Item Number: 1023594100