

2220012093

## 2960X-48TS-L

CISCO Catalyst 2960X 48-port 10/100/1000 Switch



---

## Description

Cisco Catalyst 2960-X Series Switches are fixed-configuration, stackable Gigabit Ethernet switches that provide enterprise-class access for campus and branch applications. Designed for operational simplicity to lower total cost of ownership, they enable scalable, secure and energy-efficient business operations with intelligent services and a range of advanced Cisco IOS Software features.

# Specifications

The Cisco 2960X-48TS-L is managed 48-port switch with 48 auto-sensing 10/100/1000 ports and 4 Gigabit Ethernet SFP ports.

## ENVIRONMENT

Operating temperature	23° to 113°F (-5°to 45°C)
-----------------------	---------------------------

Operating relative humidity	10% to 95% noncondensing
-----------------------------	-----------------------------

## ELECTRICAL CHARACTERISTICS

Frequency	50/60 Hz
-----------	----------

Maximum heat dissipation	169.58 BTU/hr
--------------------------	---------------

AC voltage	100 / 240 VAC
------------	---------------

Current	1 / 0.5 A
---------	-----------

Maximum power rating	49.7 W
----------------------	--------

## DIMENSIONS & WEIGHT

Dimensions (W x D x H)	445 x 279 x 45 mm
------------------------	-------------------

Weight	4.2 kg
--------	--------

Mounting	Rack Mountable, 1HU
----------	---------------------