

2220012154

SFP-10G-LRM

CISCO 10GBase-LRM SFP+ 10GbE transceiver module for both multimode and single-mode fibers



Description

The Cisco 10GBASE-LRM Module supports link lengths of 220m on standard Fiber Distributed Data Interface (FDDI) grade multimode fiber (MMF). To make sure that specifications are met over FDDI-grade, OM1 and OM2 fibers, the transmitter should be coupled through a mode conditioning patch cord. No mode conditioning patch cord is required for applications over OM3 or OM4.

Specifications

CABLING

Type	Multimode and Single-Mode
	* 62.5/125 µm or 50/125 µm (core/cladding) diameter, wavelength (nm) 1310
	* 9/125 µm (core/cladding) diameter, wavelength (nm) 1310
Maximum distance	220 m (62.5 µm core diameter, 500 MHz*km bandwidth)
	100 m (50 µm core diameter, 400 MHz*km bandwidth)
	220 m (50 µm core diameter, 500 MHz*km bandwidth)
	300 m (G.652 Single-mode)

DIMENSIONS & WEIGHT

Dimensions (W x D x H)	13.4 x 56.5 x 8.5 mm
Weight	0.075 kg

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.