

2310111042

MIC-7230-PB4

MIC Dynamic 7000, Alu, 1080p





Description

This item has been replaced by item number 2310111109

The MIC7000 camera has an advanced PTZ platform that was designed using Bosch's domain expertise in material engineering, mechanical design, intelligent imaging, and video streaming. The camera complies to some of the toughest industry standards such as IK10 and IP68/NEMA 6P for extreme mechanical strength and durability. The camera is designed using the latest technology in intelligent imaging and video streaming. Thanks to the intelligent coding and Content-Based Imaging Technology (CBIT), the HD module delivers highresolution video even under challenging light conditions at very low bit rates.

- Exceptional strength and ruggedness for any outdoor, industrial, or commercial surveillance application
- Choice of starlight (720p50/60) or dynamic (1080p25/30) camera technology with highperformance 30x lens for scenes with limited or non-uniform illumination

page 1/3

- Field-installable combo illuminator (IR/white light) with 3D diffuser and constant light for applications requiring recognition-level details in monochrome mode or even in color mode
- Simple installation with new hinged DCA mounting accessory and new cable design saves time and installation-related costs
- Exceptional system intelligence offers advance video analytics (IVA) and Content-Based Imaging Technology (CBIT)

page 2/3

Specifications

GENERAL

Dimension (WxHxD) 217,75 x 368,89 x 178,33 mm Weight 6,7 Kg Without illuminator: RJ- 45 100 Base-TX Ethernet PoH (60 W midspan; NPD-6001A), or HPoE 95 W midspan (NPD-9501A) With illuminator: HPoE 95 W midspan Power camera 24 VAC (power supply)			
Without illuminator: RJ- 45 100 Base-TX Ethernet PoH (60 W midspan; NPD-6001A), or HPoE 95 W midspan (NPD-9501A) With illuminator: HPoE 95 W midspan	Dimension (WxHxD)	•	
45 100 Base-TX Ethernet PoH (60 W midspan; NPD-6001A), or HPoE 95 W midspan (NPD-9501A) With illuminator: HPoE 95 W midspan	Weight	6,7 Kg	
Power camera 24 VAC (power supply)	Power network	45 100 Base-TX Ethernet PoH (60 W midspan; NPD-6001A), or HPoE 95 W midspan (NPD-9501A) With illuminator: HPoE 95 W	
	Power camera	24 VAC (power supply)	

Accessories





MIC-ALM-WAS-24

Alarm / washer interface board for MIC IP cameras

MIC-DCA-HB

MIC hinged alu bracket