

2320000619

## SEAS O-TV/R-IEC

TV/Radio outlet (incl. cover) (std.) for IEC-conn.



---

## Description

New outlet that comply with the latest industry standards.

Designed for marine use covering the complete TV and Radio frequency worldwide as well as optional Ethernet and fiber inserts.

The double isolation make the outlet free from interference and grounding, which is common in many systems today.

Surge protection makes it suitable for digital signals. For each splitter or tap-off output you need one SEAS multi outlet.

# Specifications

## TECHNICAL SPECIFICATION

Size	(H) 86 x (W) 86 x (D) 32 mm	
Cover	White RAL 9010	
Weight	150g	
Frequency range	TV	47-68 MHz; 130-1.000 MHz
Frequency range	R	0.1-30 MHz; 88-108 MHz
Through loss	IN-TV	47~68 MHz 1dB typ. 2.8 dB max.
		130~1000 MHz 1dB . 1.5dB max.
Isolation	IN-R	0.1~30 MHz 2.5 dB typ. 4 dB max.
		88~108 MHz 1 dB typ. 1.8 dB max.
		47-68 MHz 12 dB min.
Return loss	TV-R	88-108 MHz 12 dB min.
		130-1000 MHz 12 dB min.
		5-68 MHz MHz 10 dB min.
	IN	88-108 MHz 12 dB min.
		130-1000 MHz 14 dB* min, but >10dB
		47-68 MHz 10 dB min.
Connectors	TV	130-1000 MHz 14 dB* min, but >10dB
		88-108 MHz 10 dB min.
	Input	Terminal block
	R	IEC female
Impedance	TV	IEC male
	R	IEC female
		75 Ohms

Impedance	75 Ohms
Galvanic isolation	400 V
	Optional 2.5 kV with reduced frequency range only special order
Screening factor	TV 35 dB, R 43dB
IP rating	IP20