

2320000620

## SEAS O-TV/R-F

TV/Radio outlet (incl. cover) (std.) for F-connector



---

## Description

New outlet that comply with the latest industry standards.

Designed for marine use covering the complete TV and Radio frequency worldwide as well as optional Ethernet and fiber inserts.

The double isolation make the outlet free from interference and grounding, which is common in many systems today.

Surge protection makes it suitable for digital signals. For each splitter or tap-off output you need one SEAS multi outlet.

# Specifications

## TECHNICAL SPECIFICATION

Size	(H) 86 x (W) 86 x (D) 32 mm
Cover	White RAL 9010
Weight	150g
Frequency range	TV 47-68 MHz; 130-1.000 MHz
Frequency range	R 0.1-30 MHz; 88-108 MHz
Through loss	IN-TV 47~68 MHz 1dB typ. 2.8 dB max. 130~1000 MHz 1dB . 1.5dB max.
	IN-R 0.1~30 MHz 2.5 dB typ. 4 dB max. 88~108 MHz 1 dB typ. 1.8 dB max.
Isolation	TV-R 47-68 MHz 12 dB min. 88-108 MHz 12 dB min. 130-1000 MHz 12 dB min.
Return loss	IN 5-68 MHz MHz 10 dB min. 88-108 MHz 12 dB min. 130-1000 MHz 14 dB* min, but >10dB
	TV 47-68 MHz 10 dB min. 130-1000 MHz 14 dB* min, but >10dB
	R 88-108 MHz 10 dB min.
Connectors	Input Terminal block
	TV F female
	R F female
	Fiber SC/APC Receptable
	CAT6 RJ-45

Impedance	75 Ohms
Galvanic isolation	400 V
	Optional 2.5 kV with reduced frequency range only special order
Screening factor	TV 35 dB, R 43dB
Operation temp.	-40 to +60°C
Approvals	CE50083-2:2006 (Class B)