zenitel

DATASHEET



1008111901

TCIS-C1 | Audio Intercom

IP and SIP Intercom

- Durable yellow thermoplastic front plate with two labelled call buttons and braille.
- Advanced Audio Technology - High sound pressure levels, automatic volume gain control, and active noise and echo cancellation for superior clarity.
- Weather-Resistant (IP66) & Robust (IK08)
- ONVIF Conformant - Seamless video and device integration
- Flexible Installation - Options for wall or flush mounting
- Seamless Integration - Fully compatible with Zenitel Connect Pro, ICX-AlphaCom, IC-EDGE, and SIP-based systems.

Zenitel Connect | Door Intercom | SIP | ONVIF Conformant | UL Certified Intercom | IC-Edge

ICX-AlphaCom | IP66 | IK08 | HD Voice

Description


This audio intercom is engineered with advanced audio technologies to ensure optimal intelligibility in challenging environments. It features wideband HD voice for enhanced clarity, Open Duplex for natural two-way communication, and integrated noise suppression and acoustic echo cancellation algorithms for clean audio in noisy settings. The unit incorporates a high-sensitivity MEMS microphone, a 10W Class D amplifier for high-output performance, and a custom-engineered speaker grille optimized for acoustic dispersion and protection. Backed by over 70 years of expertise in audio and communication systems, this product delivers consistently superior sound quality across diverse applications.

Technical Dimensions

www.zenitel.com info@zenitel.com Last revision date: 2026-06-03 10:50

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.



All dimensions in mm

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

AUDIO	
Max SPL @ 0.5m	106 dB
Codecs	G.711, G.722, G.729
Frequency range, G.722 Codec	200 Hz – 7000 Hz
Audio technology	Full open duplex, switched open duplex
	Sound level detection (scream alarm)
	Automatic gain control
	Automatic volume control (AVC)
	Acoustic Echo Cancellation (AEC)
	Noise cancellation
Internal speaker amplifier	10 W class D
Internal speaker	200 Hz – 7000 Hz
Microphone technology	Digital MEMS, omnidirectional microphone

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

NETWORKING AND PROTOCOLS

Application Protocols	SIP, SIPS, HTTP, HTTPS, TFTP, RTP, SRTP, RTCP, RTSP, DHCP, SNMP, Vingtor-Stentofon CCoIP®, NTP, ONVIF, WS-Discovery
IP Versions	IPv4 & IPv6
LAN protocols	Power over Ethernet (IEEE 802.3 a-f), Network Access Control (IEEE 802.1x)
Supervision functions	Keep alive test, tone test, status reports
SIP support	RFC 3261 (SIP base standard) RFC 3515 (SIP refer) RFC 2976 (SIP info), SIP using TLS, RFC 5630 SIPS URI scheme
DTMF support	RFC 2833, RFC 2976 (SIP info)
Integration and API	Connected to ICX-AlphaCom through AlphaCom protocol ACDP
	Connected to Zenitel Connect Pro though Zenitel Link
	ONVIF

HARDWARE

Ethernet connector	1 x RJ 45
General inputs and outputs	6 (configurable)
Outputs	12mA as LED drivers
Change-over relay (NO+NC+COM)	SELV
Power options	PoE or 24 VDC (16 – 48 V)
PoE (power over Ethernet)	IEEE 802.3af standard
Power consumtion	Idle 1.8W, max 12W (depending on volume)
Button backlight	LED
Call indication	Icons/colors for hearing impaired
Door open indication	Icons/colors for hearing impaired

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

CONSTRUCTION

Dimensions (HxWxD)	180 x 120 x 73 mm / 7.1” x 4.7” x 2.9”
Dimensions after flush mount	180 x 120 x 24 mm / 7.1” x 4.7” x 0.9”
Dimensions with on wall box	180 x 120 x 86 mm / 7.1” x 4.7” x 3.4”
Weight	0.8 kg / 1.8 lbs
Faceplate material	3 mm / 0.12” PMMA, colour printed on back side
Base / frame material	3 mm / 0.12” Aluminum alloy - A413.0, AlSi12Fe, painted
Electronics cover material	Polycarbonate (translucent)
Gasket material	Silicone rubber
Loudspeaker poke protection, small diameter objects	Stainless steel mesh, acoustically transparent

ENVIRONMENTAL COMPLIANCES

IP rating	IP66
IK rating	IK08
Operating temperature range	-40° to 70° C / -40° to 158 ° F
Storage temperature range	-40° to 70° C / -40° to 158 ° F
Realtive humidity	< 95% not condensing
Corrosion	Salty mist, tested according to EN60945
Vibration	Tested according to EN60945

APPROVALS

EMC	EN 61000-6-1, EN 61000-6-3, EN 50121-4, FCC part 15
Safety	UL 62368-1, IEC 62368-1, IECEE CB
Sustainability	RoHS, REACH

OTHER SPECIFICATIONS

Country of manufacture	Poland
Warranty	2 Years standard warranty, extendible up to total of 5 years (additional fee)

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company’s Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Accessories



TA-1

Turbine Compact Onwall Back Box

Item Number: 1008140010



TA-2

US 2-Gang 3½" Deep Backbox

Item Number: 1008140020



TA-5

Bracket for US 2 GANG Double Depth Back Box

Item Number: 1008140050



Touchless Sensor

Item Number: 2390020100



TA-14

Microphone windshield for TCIS / TCIV

Item Number: 1008140140



1600 Turbine Plate w/TA-18 USA Box

Item Number: 107216008140



Stainless Steel backbox with hood

Item Number: 1072104300



Stainless Steel backbox with hood, yellow

Item Number: 1072104900



Stainless Steel backbox, no hood, yellow

Item Number: 1072104000

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Used With



Emergency Communication Wall Unit with Turbine Cut-Out

1602 Deluxe Wall Unit Slim with Turbine Cut-Out

Item Number: 2809016028



Emergency Communication Wall Unit

1602 Deluxe Wall Unit Slim

Item Number: 2809016029



Emergency Communication Wall Unit

1602 Deluxe Stanchion Wall Unit

Item Number: 2809016020



Emergency Communication Wall Unit

1602 Wall Unit with Mass Notification

Item Number: 2809016022



Emergency Communication Wall Unit with Turbine Cut-Out

1603 Economy Wall Unit Slim

Item Number: 2809016038



Emergency Communication Wall Unit

1603 Economy Wall Unit Slim

Item Number: 2809016039



Emergency Communication Wall Unit

1603 Economy Wall Unit

Item Number: 2809016030

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.