

2310111101

## OC-PTZ-2MP

Outdoor IP Camera, PTZ, 2MP, SST 316L, Hi-PoE&amp;24VAC

 DISCONTINUED

- ✓ PTZ camera in 316L stainless steel housing
- ✓ Very good low-light sensitivity
- ✓ 23x optical zoom.



## Description

VINGTOR-STENTOFON Anti-Corrosion OC-PTZ-2MP smart PTZ Network Dome Camera is able to effectively avoid acidic and neutral salt fog corrosion. OC-PTZ-2MP is also able to capture high quality colored images in dim light environment with its cutting-edge low illumination level down to 0.002Lux (color). Embedded with 1/1.9" progressive scan CMOS chip makes true WDR (120dB) and 2MP real-time resolution possible. With the 23X optical zoom Day/Night lens, the camera offers more details over expansive areas. The Anti-Corrosion PTZ camera also features a wide range of smart functions, including face detection, intrusion detection, line crossing detection and audio exception, benefitting users with great improvement on security efficiency, more importantly, with key events / objects being recorded for further forensic needs. These features, combined with smart tracking, which enables the camera to detect any progressively moving object and follow it within the camera's area of coverage without fault. Smart Defog and EIS (Electronic Image Stabilization) are further supported to improve image quality in challenging conditions.

### Key Features

- ✓ Anti-corrosion stainless steel, effectively avoid acidic and neutral salt fog corrosion
- ✓ 1/1.9" HD CMOS sensor
- ✓ 2MP(1920\*1080) Full HD
- ✓ 23X Optical Zoom
- ✓ Ultra-low illumination
- ✓ 120dB True WDR
- ✓ 316L stainless steel

- ✓ WF2, C5-M, NEMA 4X anti-corrosion standard
- ✓ IP67 standard
- ✓ Smart Tracking, Smart Detection, EIS, Defog
- ✓ Hi-PoE / 24VAC power supply

#### Function description

##### Basic function

- ✓ Anti-corrosion stainless steel, effectively avoid acidic and neutral salt fog corrosion
- ✓ WF2, C5-M, NEMA 4X anti-corrosion standard
- ✓ IP67 standard
- ✓ High performance CMOS, up to 1920x1080 resolution
- ✓  $\pm 0.1^\circ$  Preset Accuracy
- ✓ ONVIF(Open Network Video Interface Forum), CGI(Common Gateway Interface), PSIA(Physical Security Interoperability Alliance), to ensure greater interoperability between different platforms and compatibility
- ✓ 3D intelligent positioning function
- ✓ 3D DNR
- ✓ 7 alarm inputs and 2 alarm outputs
- ✓ Scheduled PTZ movement

##### Smart function:

- ✓ Smart tracking modes: Manual/Panorama/ Intrusion trigger/ Line crossing trigger/ Region entrance trigger/ Region exiting trigger, support smart tracking when patrol between multiple scenarios
- ✓ Smart detection: Support Face detection, Intrusion detection, Line crossing detection, Audio exception detection, Region entrance detection, Region exiting detection
- ✓ Smart recording: Support edge recording, support dual-VCA for smart search in smart NVR
- ✓ Smart image processing: Support defog, HLC, EIS
- ✓ Smart codec: Low bit rate, ROI

##### Camera function:

- ✓ Auto iris, auto focus, auto white balance, backlight compensation and auto day & night switch
- ✓ Min. Illumination: 0.002Lux@(F1.5,AGC ON)(Color), 0.0002Lux@(F1.5,AGC ON)(B/W)
- ✓ Support privacy mask with multiple colors and mosaics on polygonal areas

##### PTZ function:


- ✓ 360° endless pan range and -20°~ 90° tilt range
- ✓ 540°/s Pan Preset Speed and 400°/s Tilt Preset Speed
- ✓ 0.1°~ 300°/s Manual Pan Speed and 0.1°~ 240°/s Manual Tilt Speed
- ✓ 300 presets programmable; preset image freezing capability
- ✓ 8 patrols, up to 32 presets per patrol
- ✓ 4 patterns, with the recording time not less than 10 minutes per pattern
- ✓ Proportional zoom function

- ✓ Park action: auto call up of PTZ movement, after a defined time of inactivity
- ✓ Power-off memory: restore PTZ & Lens status after reboot

Network function:

- ✓ H.264/MJPEG/MPEG4 video compressio
- ✓ H.264 encoding with Baseline/Main/High profile
- ✓ ROI(Region of Interest) encoding(support 24 areas with adjustable levels)
- ✓ Built-in Web server
- ✓ Onboard storage, up to 128GB
- ✓ Support up to 8 NAS storage; Edge recording(transmit the videos from SD card to the NAS after network resumed) HTTPS encryption and IEEE 802.1X port-based network access control
- ✓ Support trip-streams
- ✓ Multiple network protocols supported: IPv4/Ipv6, HTTP, HTTPS, 802.1X, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE
- ✓ 1 audio input and 1 audio output

## Technical Dimensions



# Specifications

## CAMERA MODULE

Image Sensor	1/1.9" Progressive Scan CMOS
Min. Illumination	F1.5, AGC On: Color: 0.002 lux, B/W: 0.0002 lux
Max. Image Resolution	1920×1080
Focal Length	5.9-135.7mm, 23x
Digital Zoom	16X
Zoom Speed	Approx.4.4s(Optical Wide-Tele)
Angle of View	59.8-3.0 degree (Wide-Tele)
Min. Working Distance	10-1500mm(Wide-Tele)
Aperture Range	F1.5~F3.4
Focus Mode	Auto / Semiautomatic / Manual
WDR	120dB
S / N Ratio	≥ 55dB
Shutter Time	50Hz: 1~1/30,000s; 60Hz: 1~1/30,000s
AGC	Auto / Manual
White Balance	Auto / Manual /ATW/Indoor/Outdoor/Daylight lamp/Sodium lamp
Day & Night	IR Cut Filter
Privacy Mask	24 privacy masks programmable; optional multiple colors and mosaics
Enhancement	3D DNR, EIS, Defog, HLC/BLC, SVC

## PAN AND TILT

Range	Pan:360° endless; Tilt: - 20°~90°(Auto Flip)
Speed	Pan Manual Speed: 0.1°~300°/s, Pan Preset Speed: 540°/s  Tilt Manual Speed: 0.1°~240°/s, Tilt Preset Speed: 400°/s
Number of Preset	300
Patrol	8 patrols, up to 32 presets per patrol
Pattern	4 patterns, with the recording time not less than 10 minutes per pattern
Park Action	Preset / Patrol / Pattern / Auto scan / Tilt scan / Random scan / Frame scan / Panorama scan
Scheduled Task	Preset / Patrol / Pattern / Auto scan / Tilt scan / Random scan / Frame scan / Panorama scan/Dome reboot/Dome adjust/Aux output

## SMART FEATURES

Smart tracking	Manual/ Panorama/ Intrusion trigger/ Line crossing trigger/ Region entrance trigger/ Region exiting trigger Smart tracking when patrol between multiple scenarios
Smart detection	Face detection, Intrusion detection, Line crossing detection, Audio exception detection, Region entrance detection, Region exiting detection
ROI encoding	Support 24 areas with adjustable levels

## ALARM

Alarm I/O	7/2
Alarm Trigger	Face detection, Intrusion detection, Line crossing detection, Region entrance, Region exiting, Audio exception detection, Motion detection, Dynamic analysis, Tampering alarm, Network disconnect, IP address conflict, Storage exception
Alarm Action	Preset, Patrol, Pattern, Micro SD/SDHC card recording, Relay output, Notification on Client

## INPUT / OUTPUT

Monitor Output	1.0V[p-p] / 75Ω, NTSC (or PAL) composite, BNC
Audio Input	1 Mic in/Line in interface, line input: 2-2.4V[p-p]; output impedance: 1KΩ, ±10%
Audio Output	1 Audio output interface, line level, impedance: 600Ω

## NETWORKING AND PROTOCOLS

Ethernet	10Base-T / 100Base-TX, RJ45 connector
Main Stream	50Hz: 25fps(1920×1080, 1280×960, 1280×720); 60Hz: 30fps(1920×1080, 1280×960, 1280×720)
Sub Stream	50Hz: 25fps(704×576, 352×288, 176×144); 60Hz: 30fps(704×480, 352×240, 176×120)
Third Stream	50Hz: 25fps(1920×1080, 1280×960, 1280×720, 704×576, 352×288, 176×144)
	60Hz: 30fps(1920×1080, 1280×960, 1280×720, 704×480, 352×240, 176×120)
Image Compression	H.264/MJPEG/MPEG4, H.264 encoding with Baseline/Main/High profile
Audio Compression	G.711ulaw/G.711alaw/G.726/ MP2L2/G.722/PCM
Protocols	IPv4/IPv6, HTTP, HTTPS, 802.1X, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, ICMP, DHCP, PPPoE
Simultaneous Live View	Up to 20 users
Mini SD Memory Card	Support up to 128GB Micro SD/SDHC/SDXC card. Support Edge recording
User/Host Level	Up to 32 users,3 Levels: Administrator, Operator and User
Security Measures	User authentication (ID and PW); Host authentication (MAC address); IP address filtering

## SYSTEM INTEGRATION

Application programming	Open-ended API, support ONVIF, PSIA , CGI and Genetec
Web Browser	IE 7+, Chrome 18 +, Firefox 5.0 +, Safari 5.02 +, support multi-language
RS-485 Protocols	HIKVISION, Pelco-P, Pelco-D, self-adaptive
Power	Hi-PoE&24 VAC, Max.60W
Working Temperature	-40°C ~ 65°C (-40°F ~ 149°F)
Humidity	90% or less
Anti-corrosion standard	WF2, C5-M, NEMA 4X
Protection Level	IP67, IK10, TVS 4,000V lightning protection, surge protection and voltage transient protection
Certification	FCC, CE, UL, RoHS, IEC/EN 61000, IEC/EN 55022, IEC/EN 55024, IEC /EN60950-1
Dimensions	Φ262(mm) ×330(mm)
Weight (approx.)	10kg (approx.)

## ACCESSORIES

2310111123	SST 316L Junction box for OC-series cameras
2310111126	OC-PTZ-WB Wall-mount bracket for OC-PTZ-2MP
2310111125	60W High PoE midspan (PoE injector) 110-230VAC

## Accessories





LAS60-57CN-RJ45

60W High PoE midspan (PoE injector) 110-230VAC



OC-PTZ-WB Wall Mount Bracket

Anticorrosive wall mount bracket for OC-PTZ-2MP CCTV Camera.