

2211000654

SMART1-SAS

Appliance Server for SMART1 Manager, CMS and virtual PBX.

A tailored box, powerful to host the CMS, SMART1 Manager and a virtual PBX at the same time.

Every customer can choose by themselves which applications should be used on each site.

Description

The Vingtor-Stentofon SMART1 Appliance Server (SAS), the host for our virtual applications, is intended to minimize the hardware used at customer premises to a minimum. It supports a flexible and versatile setup and both SMART1 Manager, CMS as well as a virtual PBX will be pre-installed from the beginning.
Our customers can freely choose by themselves which applications that should be used for each site. We provide "all in one" for those who choose that option or "pick and choose" for those who prefer this.

SAS is intended to be installed in a 19" rack and runs on any power between 9-32Vdc. This keeps the cost for battery backup at a minimum. Saving both environment and electricity. The power cable is not included.

www.zenitel.com info@zenitel.com Last revision date: 2023-09-18 11:18

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

GENERAL	
Mechanical Hardware	1U rack, depth 237mm
Processor	Intel Atom C2558 Quad Core
System Memory	8GB 1600MHz ECC DDR3. Option up to 64 GB DDR3 ECC
Storage	1 x 2.5” 120 GB SATA SSD
Graphics	2 x VGA, Aspeed AST 2400 BMC
Network	4 x GB Ethernet ports, Virtual Machine Device Queues reduce I/O overhead, Supports 10BASE-T, 100BASETX and 1000BASE-T, RJ45 output, 1 x RJ45 dedicated IPMI
Management	Support for Intelligent Platform Management Interface v.2.0, IPMI 2.0 with virtual media over LAN and KVM-over-LAN support, NMI, SuperDoctor® 5, Watch Dog
Operating System	VM Ware vSphere Hypervisor (ESXI)
Power Supply	70W DC power supply, 9-32 VDC input, Max power consumption 20W

Used With



SMART1-SM-HS

Android based DECT Smartphone with WiFi.

Item Number: 2211100521



SMART1-SP-HS

Easy to use lightweight DECT handset.

Item Number: 2211100522



SMART1-AP

SMART1 multicell base station

Item Number: 2211000645

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company’s Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.