

2220012096 SG350-28

Cisco SG350-28 28-port Gigabit Managed Switch



# Description

The Cisco 350 Series, part of the Cisco Small Business line of network solutions, is a portfolio of affordable managed switches that provides a reliable foundation for your business network. These switches deliver the features you need to improve the availability of your critical business applications, protect your sensitive information, and optimize your network bandwidth to deliver information and applications more effectively. Easy to set up and use, the Cisco 350 Series provides the ideal combination of affordability and capabilities for small businesses, and helps you create a more efficient, better-connected workforce.

#### page 1/2

### www.zenitel.com

#### info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

# Specifications

The Cisco SG350-28 is managed 28-port switch with 24 auto-sensing 10/100/1000 ports, 2 Gigabit Ethernet combo ports and 2 SFP ports.

# ENVIRONMENT

| Operating temperature          | 32°to 113°F (0°to 45°C)             |
|--------------------------------|-------------------------------------|
| Operating relative<br>humidity | 10% to 90%, relative, noncondensing |

# **ELECTRICAL CHARACTERISTICS**

| Frequency                   | 50-60 Hz      |
|-----------------------------|---------------|
| Maximum heat<br>dissipation | 67.9 BTU/hr   |
| AC voltage                  | 100 / 240 VAC |
| Maximum power rating        | 19.7 / 19.9 W |

## **DIMENSIONS & WEIGHT**

| Dimensions (W x D x H) | 440 x 202 x 44 mm   |
|------------------------|---------------------|
| Weight                 | 2.75 kg             |
| Mounting               | Rack Mountable, 1HU |

### www.zenitel.com

### info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.