



2220012340

ISR4331V/K9

Cisco ISR4331-V/K9 Voice Bundle(PVDM4-32,UC License,CUBEE10)

This item has been replaced with the new upgraded Voice Gateway:

Grandstream Voice Gateway (zenitel.com)

Description

The Cisco 4000 Series Integrated Services Routers (ISR) revolutionize WAN communications in the enterprise branch. With new levels of built-in intelligent network capabilities and convergence, the routers specifically address the growing need for application-aware networking in distributed enterprise sites. These locations tend to have lean IT resources. But they often also have a growing need for direct communication with both private data centers and public clouds across diverse links, including Multiprotocol Label Switching (MPLS) VPNs and the Internet.

page 1/2

Specifications

TECHNICAL SPECIFICATIONS

3x Total onboard WAN or LAN 10/100/1000 ports

2x RJ-45-based ports

2x SFP-based ports

1x Enhanced service-module

slots

2x NIM slots

1x Onboard ISC slot

PVDM4-32

CUBEE10

IP Base + Unified

Communications License: Cisco Unified Communications Manager Express, Survivable Remote Site Telephony (SRST)

Aggregate Throughput 100 Mbps to 300 Mbps

ENVIRONMENT

Operating temperature 32 to 104°F (0 to 40°C)

Operating relative humidity 5% to 85%

ELECTRICAL CHARACTERISTICS

Maximum heat dissipation853.03 BTU/hrAC voltage100 / 240 VACCurrent3 / 1.3 AMaximum power rating250 WAC input surge current60 A peak and less than 5 Arms per half cycle	Frequency	50 to 60 Hz
Current 3 / 1.3 A Maximum power rating 250 W AC input surge current 60 A peak and less than 5 Arms	Maximum heat dissipation	853.03 BTU/hr
Maximum power rating 250 W AC input surge current 60 A peak and less than 5 Arms	AC voltage	100 / 240 VAC
AC input surge current 60 A peak and less than 5 Arms	Current	3 / 1.3 A
ACTIONIT SUITE CUITENT	Maximum power rating	250 W
	AC input surge current	·

DIMENSIONS & WEIGHT

Dimensions (W x D x H)	438.15 x 438.15 x 44.45 mm
Weight	6.2 kg
Mounting	Rack Mountable, 1HU

page 2/2