

2220012344

CISCO ISDN Gateway

CISCO ISDN Gateway 4331 w/ 10 SIP to SIP trunk licenses



Description

The Cisco 4000 Series Integrated Services Routers (ISR) revolutionize WAN communications in the enterprise branch. With new levels of built-in intelligent network capabilities and convergence, the routers specifically address the growing need for application-aware networking in distributed enterprise sites. These locations tend to have lean IT resources. But they often also have a growing need for direct communication with both private data centers and public clouds across diverse links, including Multiprotocol Label Switching (MPLS) VPNs and the Internet.

Specifications

TECHNICAL SPECIFICATIONS

3x Total onboard WAN or
LAN 10/100/1000 ports

2x RJ-45-based ports

2x SFP-based ports

1x Enhanced service-
module slots

2x NIM slots

1x Onboard ISC slot

1x Cisco 1-port T1/E1
Multiflex Trunk Voice/Clear-
channel Data

PVDM4-32

CUBEE10

IP Base + Unified
Communications License:
Cisco Unified
Communications Manager
Express, Survivable Remote
Site Telephony (SRST)

Aggregate Throughput 100
Mbps to 300 Mbps

ENVIRONMENT

Operating temperature 32 to 104°F (0 to 40°C)

Operating relative humidity 5% to 85%

ELECTRICAL CHARACTERISTICS

Frequency 50 to 60 Hz

Maximum heat dissipation 853.03 BTU/hr

AC voltage 100 / 240 VAC

Current 3 / 1.3 A

Maximum power rating 250 W

AC input surge current 60 A peak and less than 5
Arms per half cycle

DIMENSIONS & WEIGHT

Dimensions (W x D x H)	438.15 x 438.15 x 44.45 mm
Weight	6.2 kg
Mounting	Rack Mountable, 1HU