

2310101057

## SD436-PSGE1-X

Outdoor Camera Dome, SST, day-night, PTZ, 36x optical zoom

DISCONTINUED



- ✓ All Stainless Steel Construction
- ✓ Built-in Back Box Memory
- ✓ Integrated Passive UTP Circuit
- ✓ 7 Alarm Inputs; 2 Programmable Auxiliary Outputs
- ✓ Built-in Surge and Limited Lightning Protection
- ✓ Bubble Constructed of Optically Clear Acrylic
- ✓ Environmental Pendant Mount
- ✓ Outdoor Applications
- ✓ 36x Optical Zoom, Environmental Pendant Mount, Grey Stainless Steel Housing, Clear Lower Dome, NTSC

 IP66

### Description

The SD436-PSGE1-X is designed for harsh environmental installations and meets NEMA Type 4X and IP66 standards. The components provide added protection against corrosive conditions.

# Specifications

## DESCRIPTION

Size (WxH)	216.4 x 276.9 mm
Weight	4.5 kg
Input Voltage	18 to 32 VAC; 24 VAC nominal
Power Consumption	24 VAC: 73 VA , 24 VDC: 3 A
Fuse	1.6 A
Operating Temperature	-51.11°C to 60°C
Lens Type	Motorized Zoom
Lens Size	36X
Certifications	CE, Class B; FCC, Class B; UL/cUL Listed; C-Tick; S Mark for Argentina; NEMA Type 4X, IP66 standards.

## Accessories



### IDM4012SS

Bracket for Spectra dome stainless steel SD-429 & S6230