

2310120094

HD 19T21 STD Marine Display

19" Marine display IEC60945 approved



- ✓ High Quality TFT with LED Backlight
- ✓ 19.0 inch viewable image size, Aspect Ratio 5:4
- ✓ TFT active-matrix liquid crystal panel
- ✓ MVA (Multi-domain Vertical Alignment) LCD Technology

Description

HD 19T21 STD which is part of the "Series X Displays" offer the ultimate in performance, convenience, state of the art design and enduring quality for system integrators and boat builders. Series X products offer a range of feature sets optimized for varying requirements and applications.


Marine Display

The Series X display range is a flexible monitor solution designed and type approved for the professional maritime segment, where reliability and long life time are key prerequisites for the industry. The product range combines stunning design and technology with innovative features and options, making it all that the integrator needs for top class type-approved marine systems.

The entry level STD models provide a wide choice of display size and format for shipboard applications where simple data input (DVI & VGA) is required. Be it for ship navigation or automation, this range with all it's possible options provides a robust and cost effective platform from which to display and manage data.

Series X displays feature Glass Display Control™, LED Backlight Technology, full dimming and multipower as standard, and can also accomodate and combine a number of options such as multitouch screen and optical bonding.

Technical Dimensions



Specifications

TFT TECHNOLOGY: PHYSICAL CONSIDERATIONS:

- High Quality TFT with LED Backlight
- 19.0 inch viewable image size, Aspect Ratio 5:4
- TFT active-matrix liquid crystal panel
- MVA (Multi-domain Vertical Alignment) LCD Technology

TFT CHARACTERISTICS:

| | |
|---------------------|---|
| Native Resolution | 1280 x 1024 |
| Pixel Pitch (RGB) | 0.294 (H) x 0.294 (V) mm |
| Response Time | 35ms (typical), "black" to "white" |
| Contrast Ratio | 1500:1 (typical) |
| Light Intensity | 350 cd/m ² (typical) |
| Viewable Angle | +/- 85 deg. (typical) (Up/Down/Left/Right) |
| Active Display Area | 376.32 (H) x 301.056 (V) mm |
| Max Colors | 16.7 million |

SUPPORTED SIGNALS:

- VGA : 640 x 480
(including 640 x 350)
- VGA : 640 x 480
(including 640 x 350)
- XGA : 1024 x 768
- SXGA : 1280 x 1024*

* Recommended for optimal picture quality

Note: Other resolutions will be scaled full screen, unit has no scaling support.

POWER SPECIFICATIONS:

| | |
|---------------------|---|
| Multi-power Supply: | 100&230VAC - 50/60Hz + 24 VDC - HD 19T21 STD- Mxx-Fxxx |
| | Note: You may connect either AC power or DC power or both. In case both sources are connected, power will be sourced from the AC input. If AC input is lost, there will be a uninterrupted switch-over to DC input. |
| Power Consumption: | Operating AC/DC Standard : 33W (typ) - 125W (max) |

SIGNAL TERMINALS:

| | |
|---------------------|---|
| • DVI-D Signal IN : | 1 x 24p DVI (female) |
| • RGB Signal IN : | 1 x 15p HD D-SUB (female) |
| • SCOM RS-422/485 : | 1 x 5-pin Terminal Block 3.81, non-isolated+Buzzer |
| • SCOM RS-232 : | 1 x 9p D-SUB (female) non-isolated+Buzzer |
| • If Touchscreen : | 1 x USB TYPE B Connector (female) |
| • AC Power IN : | 1 x Std IEC Inlet |
| • DC Power IN : | 1 x 2-pin Terminal Block 5.08 |

DIMENSIONS AND ENVIRONMENT

W:429.00 [16.89"] x
H:382.00 [15.04"] x
D:74.50 [2.93"] mm [inch]

4 x M6 VESA mounting
280x150mm, Max 12mm
deep

Weight: 7.8kg / 17.2lbs

Operating : Temperature -
15 deg. C to +55 deg. C -
Humidity up to 95%

Storage : Temperature -20
deg. C to +60 deg. C -
Humidity up to 95%

IP Rating : Protection: IP66
front - IP22 rear (EN60529)

Lifetime Considerations:
Even though the test
conditions for bridge units
provide for a maximum
operating temperature of
55°C, continuous operation
of all electronic
components should, if
possible, take place at
ambient temperatures of
only 25°C. This is a
necessary prerequisite for
long life and low service
costs.

Accessories



17 to 19 inch Monitor Mount

Monitor Mount