

2310111125

LAS60-57CN-RJ45

60W High PoE midspan (PoE injector) 110-230VAC



- ✓ Compatible With All IEEE pre 802.3af, 802.3at and Legacy Powered Devices
- ✓ Input voltage:90Vac~264Vac
- ✓ Support 300Vac input for long time work
- ✓ Output over current protection
- ✓ Short circuit protection
- ✓ MTBF $\geq 1,000,000$ hrs
- ✓ Surge protection
- ✓ CE mark
- ✓ WEEE compliant
- ✓ RoHS compliant

Description

The LAS60-57CN-RJ45 midspan is designed to extract power from a conventional twisted pair Category 5 Ethernet cable, conforming to the IEEE 802.3at Power-over-Ethernet (PoE) standard. The converter signature and control circuit provides the PoE compatibility signature and power classification required by the Power Sourcing Equipment (PSE) before applying up to 60W power to the port.

Specifications

DESCRIPTION

| | |
|-----------------------|--|
| Input Current | 2A |
| Output Voltage Range | 54V~57V |
| Output Power | 60W |
| Ports | 2x 10/100/1000M adaptive RJ45 ports, one is DATA/IN, another is PoE/DATA |
| LED Indicator | Power & PoE Status(The module operates normally when MID and END are on) |
| Base Function | Compliance to IEEE 802.3 at/af Standard for PD |
| Protection Methods | Output Over Current Protection, Short Circuit Protection |
| Operating Humidity | 5% ~ 90% |
| Weight | 473g |
| Dimension (LxWxH) | 185mmx70.8mmx37mm |
| Operating Temperature | -20 ~ 60 |

Used With



[DS-2DE4425IW-DED PTZ camera](#)

4MP 25x Network IR Speed Dome PTZ camera



[DS-2XE6422FWD-IZHRS](#)

Explosion-Proof IP Bullet Camera, 2MP, w/ wiper



[iDS-2CD7A26G0-IZHSY WDR IR Varifocal Bullet Network Camera](#)

Bullet Network Camera