

2211050107

## DECT Repeater

DECT repeater 4-ch, multi-cell wo/ power supply



---

### Description

- ✓ Certified for use under Marine EMC requirements
- ✓ Wireless – no cabling needed
- ✓ Create coverage in a remote area
- ✓ Expand coverage in a single cell solution
- ✓ Increase coverage in hot spot areas
- ✓ Can be used with all KWS Servers
- ✓ Max 3 Repeaters per Base Station
- ✓ External power supply required

The DECT Repeater provides a larger geographical spread of the traffic channels and increases the coverage area. Mainly used in areas with limited coverage such as long hallways, stairwells and corridors. The repeater is wireless with no wired connection to the KWS DECT Server or base stations, making it very easy to install.

Product available in the following frequency bands:

- ✔ Item number 2211050104: DECT Repeater 1G9. USA & Canada. 1920–1930MHz (DECT6.0)
- ✔ Item number 2211050107: DECT Repeater 1G8. EMEA, Australia & New Zealand. 1880–1900MHz

# Specifications

## DESCRIPTION

Max. number of speech channels	Four
Typical range	Indoor: 20 - 50 m; Outdoor: 300 m
Weight	112.9 gr
Size	100 x 30 x 100 mm
Frequency Range	EMEA 1880-1900 MHz

## PRODUCT VARIANTS

2211050104	DECT Repeater. USA, Canada. 1G9 1920–1930MHz (DECT6.0)
2211050107	DECT Repeater. EMEA, Australia, New Zealand. 1G8 1880–1900MHz

## ACCESSORIES

2211050131	Repeater Programming Kit
2241100558	Power Supply for DECT Repeater

## Used With



IP DECT Server 400  
1G8 Version

Server Base Station

Item Number: 2211010200



KWS2500

DECT Rack including base station card, KWS-CPU and software license

Item Number: 2211020100



KWS8000

DECT Rack including power supply, cable and software license

Item Number: 2211020106



KWS6500

IP DECT Server for 30 users, including software licence

Item Number: 2211000150