

2220012637

Cisco 1562i - EMEA

Cisco 1562i Outdoor Wireless Access Point use in EMEA (E)

 DISCONTINUED

Description

- ✓ 802.11ac Wave 2, MU-MIMO 3x3 radio, 3 spatial streams
- ✓ PHY data rates up to 1.3 Gbps. Supporting channels up to 80 MHz wide
- ✓ High Density Experience (HDX). Best-in-class RF architecture, which provides high-performance coverage for a high density of client devices, giving the end user a seamless wireless experience.
- ✓ Integrated dual-band semi-omnidirectional antenna radome:
 - ✓ 7 dBi (2.4 GHz)
 - ✓ 4 dBi (5 GHz)
- ✓ Mobility Express
- ✓ 10/100/1000BASE-T Ethernet, autosensing (RJ-45), PoE in

Ideal for applications requiring rugged outdoor Wi-Fi coverage, the Cisco Aironet 1560 Series Access Points offer the latest IEEE 802.11ac Wave 2 radio standard in a compact, aesthetically pleasing, easy-to-deploy package.

Specifications

DESCRIPTION

| | |
|------------------------------------|--|
| 802.11ac Wave 1 and 2 capabilities | 3 x 3 MIMO with three spatial streams; Multi- and single-user MIMO; 20-, 40-, and 80-MHz channels; PHY data rates up to 1.3 Gbps (80 MHz in 5 GHz) |
| 802.11n capabilities | 3 x 3 MIMO with three spatial streams; 20- and 40-MHz channels; PHY data rates up to 450 Mbps |
| Interfaces | WAN port 10/100/1000BASE-T Ethernet, autosensing (RJ-45), PoE in; SFP port (fiber or electrical); Management console port (RJ-45); Multicolor LED; DC power input; Reset button |
| Dimensions (L x W x D) | 22.9 x 17.1 x 9.8 cm |
| Weight | 2.5 kg |
| Operating temperature | −40 to 65°C ambient air with no solar loading; −40 to 55°C ambient air with solar loading |
| Humidity | 5 - 95%, non-condensing |
| Wind resistance | Up to 100-mph sustained winds; Up to 165-mph wind gusts |
| Powering options | Universal Power of Ethernet (UPoE), 802.3at ; Cisco Power injectors |
| Power consumption | 32 W (3x3:3, full power) |

ORDER INFORMATION

ACCESS POINT VERSION

| | |
|------------|--|
| 2220012637 | Cisco 1562i Outdoor Wireless Access Point use in EMEA (E) |
| 2220012660 | Cisco 1562i Outdoor Wireless Access Point use in USA (B) |
| 2220012661 | Cisco 1562i Outdoor Wireless Access Point use in Canada (A) |

