

1152100001

ACM Advanced Conventional PA Control Unit



Description

- ✓ Type approved PA solution for conventional vessels
- ✓ Supports 6 PA zones and 3 SPA microphone panels
- ✓ Supports Vingtor-Stentofon integrated PA solution using ACM intercom station
- ✓ Logic is mounted in special 2 HU shelf for easy service
- ✓ All cables pre wired for easy installation

The Vingtor-Stentofon ACM ADVANCED CONVENTIONAL PA CONTROL UNIT combines quality and value. The module can support a single, non-redundant system mounted on one 19" shelf. This contains, main control board, multizone board (allowing several amplifiers). The Vingtor-Stentofon ACM ADVANCED CONVENTIONAL PA CONTROL UNIT is powered from Vingtor-Stentofon ACM ADVANCED redundant power module (2x230VAC).

Vingtor-Stentofon integrated solution with PA/GA is a part of a total cost effective solution.

Optional functions are: chime generator, entertainment (4 way in 6 zones), CD-player and radio, output for voice data recorder, and digital message recorder/recall for pre-recorded message output.

At delivery, the system is tested according to SOLAS requirements.

Specifications

GENERAL

Shelf size (mm)	483W x 90 H x 440D (19" 2HU)
Power	230V AC
Material	Anodized black aluminium
Connection	WDU 2.5 terminals on side plates
Cable requirements	Signal cable 0.75mm ² twisted pair outer screen
Operating temp	-15 to +55°C
Relative humidity	10% to 90% RH
PA functions	Dry contacts activated during PA announcement, Talkback input, PABX input
Tested according to	SOLAS Chapter 3