

4000016818

P-1601 PAGA Control Unit

Note: This product is only available as spare part.



Description

- ✓ Gooseneck Microphone
- ✓ RS485 data communication with MPA P-1600 Operation Unit
- ✓ 6-zone selection keys
- ✓ PA (normal paging) key
- ✓ Emergency PA key marked with red color
- ✓ Emergency PA key is protected against unauthorized use by means of time-trap functionality (the emergency PA key must be held for 1 sec before activation)
- ✓ Dimmer key
- ✓ Status LED for system A and system B
- ✓ LED indicators for all keys
- ✓ Dimmable backlight and indication LEDs
- ✓ Local mute relays
- ✓ Complies with IEC 60945 Standard for Marine Equipment

The MPA P-1601 is a full facility operator control unit in the MPA system. It is designed for flush mounting.

Specifications

MECHANICAL

| | |
|--------------------|---|
| Dimensions (WxHxD) | 144x144x43 mm (depth behind console excluding cables) |
| Weight | 0.6 kg |
| Color | RAL 9005 / Natural |
| Material | Aluminium / Steel |
| Mounting | Console |
| Fixing | 4 x M4 bolts |
| Access | Front |
| Cable Entry | Rear |
| Cable Type | 3-pair cable, twisted pairs, min. 3x2x0.5 mm ² |

ELECTRICAL

| | |
|------------------------|--|
| Power Supply | 24VDC from Control rack (+/- floating) |
| Frequency Range | 300-5000 Hz |
| Power Consumption | 7.2 W |
| Microphone Input Level | 10 mV |
| Termination | Termination Block |
| Compass Safe Distance | 80 cm |

ENVIRONMENTAL

| | |
|---------------------------|---------------------------|
| Temperature | -15°C to +55°C |
| Humidity | 20% to 80% non-condensing |
| Ingress Protection Rating | IP-44 |