

4000016931

P-1606 PAGA Access & Control Panel

Note: This product is only available as spare part.



Description

- ✓ Compliant with IEC 60945 Standard for Marine Equipment
- ✓ DNV-GL/ABS/RMRS/CCS/RINA type approval
- ✓ Compliant with NORSOK standards

The P-1606 MPA Access & Control Panel has six zone selection switches, four alarm activation buttons, and emergency PA and normal PA activation buttons. In addition, there is a push button for dimmer function and audio level meter. The P-1606 is developed for A and B systems.

Specifications

MECHANICAL

Dimensions (WxHxD)	483x177x55 mm including cables
Weight	3.5 kg
Mounting	Rack/Console
Fixing	4 x M5 bolt
Access	Front
Cable Entry	Rear (plug)
Cable Type	(flying lead) Unitronic 4x2x0.25 LiHCH

ELECTRICAL

Power Supply	24VDC from Control Rack (+/- floating)
Power Consumption	15 W
Termination	Plugs (9P D-sub) with flying leads
Heat Dissipation	10 W
Frequency Range	300 to 5000 Hz
Certification	For safe area only

ENVIRONMENTAL

Temperature	+5°C to +40°C
Humidity	20% to 80% non-condensing
Ingress Protection Rating	IP-22