



4000016715

P-5111


Desk Mount Telephone

Description

- ✓ Watertight IP-65
- ✓ Strong call tone $\geq 95\text{db (A)}$, 1m
- ✓ Shock resistant housing
- ✓ Complies with IEC 60945 Standard for Marine Equipment
- ✓ DNV-GL type approval

The P-5111 is a desk or wall mounted watertight analog telephone for industrial and exposed environments.

Technical Dimensions



Specifications

MECHANICAL

Dimensions (WxHxD)	191x317x128 mm
Weight	2.3 kg
Material	Polycarbonate
Color	RAL 9005
Mounting	Desk / Wall
Fixing	4 x M6 bolts
Access	Front
Cable Entry	Bottom
Gland Type	1 x M20, 1 x M20 blind plug, 2 x M12 blind plug

ELECTRICAL

Power Supply	Telephone line (self-contained)
Telephone line feed voltage	24-64 VDC
Ring Voltage / Frequency	30 < R < 90V / 16 < F < 68 Hz
Dial Method	PD (1.5:1 (60/40ms) or 2:1 (66.7/33.3ms)) / DTMF (ITU-T Q23)
Ringling Volume	≥ 95 dB(A) at 1 m distance
Termination	Screw terminals ≤1.5 mm ²

ENVIRONMENTAL

Temperature -25°C to +55°C
(Storage: -30°C to +70°C)

Humidity +93% (at +40°C)

Ingress Protection Rating IP-65
