



2211100117

7622 DECT Handset

DECT Handset, IP64

Description

The 7622 handset is highly durable, designed specifically for manufacturing environments, and comes with a range of features such as an alarm button, color display, and manufacturing-specific alarm icons.

- ✓ Robust operation and handling, IP64
- ✓ Exceptional voice quality without any background noise, echo, delay, or interruptions
- ✓ Color Display
- ✓ 12 different ringtones and vibration alert
- ✓ Advanced messaging
- ✓ Alarm Key
- ✓ Headset jack with amplifier for industrial headsets
- ✓ Handsfree
- ✓ Instant notifications make users aware of potentially hazardous situations
- ✓ Lone workers can send alarms in case of emergency

Specifications

GENERAL

Size	148 x 50.4 x 21.6 mm
Weight	115 g incl. battery
Operating temperature	-10 - 55° C
Charging temperature	0° - 40° C
Speech time	up to 23 (27 hours in economy mode)
Standby time	up to 118 hours
Approvals	EMC: EN 301 489-1, EN 301 489-6, Radio: EN 301 406; Safety: EN 60950-1; Drop test: IEC 60068-2-32; According to EN60529: IP 64 classified
Frequency Range	EMEA 1880-1900 MHz

ACCESSORIES

2211100125	Belt clip for 72 series and 76 series
2211100556	Charger kit for 7212, 7622 & 7642
2211100601	Spare Battery rechargeable for 72, 76-series DECT handset

Accessories



DECT Charger

Charger kit for 72-series,
76-series DECT Handsets.
Includes Power Supply
100-240V



Headset for DECT handset V2

Headset

Used With



KWS6500

IP DECT Server for 30
users, including software
licence



IP DECT Base Station

IP Base Station for
KWS6500



IP DECT Server 400 1G8 Version

Server Base Station