



2211100117

7622 DECT Handset

DECT Handset, IP64

Description

The 7622 handset is highly durable, designed specifically for manufacturing environments, and comes with a range of features such as an alarm button, color display, and manufacturing-specific alarm icons.

- ✓ Robust operation and handling, IP64
- ✓ Exceptional voice quality without any background noise, echo, delay, or interruptions
- ✓ Color Display
- ✓ 12 different ringtones and vibration alert
- ✓ Advanced messaging
- ✓ Alarm Key
- ✓ Headset jack with amplifier for industrial headsets
- ✓ Handsfree
- ✓ Instant notifications make users aware of potentially hazardous situations
- ✓ Lone workers can send alarms in case of emergency

Specifications

GENERAL

| | |
|-----------------------|---|
| Size | 148 x 50.4 x 21.6 mm |
| Weight | 115 g incl. battery |
| Operating temperature | -10 - 55° C |
| Charging temperature | 0° - 40° C |
| Speech time | up to 23 (27 hours in economy mode) |
| Standby time | up to 118 hours |
| Approvals | EMC: EN 301 489-1, EN 301 489-6, Radio: EN 301 406; Safety: EN 60950-1; Drop test: IEC 60068-2-32; According to EN60529: IP 64 classified |
| Frequency Range | EMEA 1880-1900 MHz |

ACCESSORIES

| | |
|------------|---|
| 2211100125 | Belt clip for 72 series and 76 series |
| 2211100556 | Charger kit for 7212, 7622 & 7642 |
| 2211100601 | Spare Battery rechargeable for 72, 76-series DECT handset |

Accessories



DECT Charger

Charger kit for 72-series,
76-series DECT Handsets.
Includes Power Supply
100-240V



Headset for DECT handset V2

Headset

Used With



KWS6500

IP DECT Server for 30
users, including software
licence



IP DECT Base Station

IP Base Station for
KWS6500



IP DECT Server 400 1G8 Version

Server Base Station