zenitel

DATASHEET

4000016479

HP-30

Horn Loudspeaker, 30W, 20 Ohm, IP67



- Suitable for outdoor and indoor installation
- IP67

Onboard communication IP67

Description


The HP-30 is a compact 30 W horn speaker delivering a powerful 110 dB SPL at 1W/1m. Built from durable polyamide and rated IP67, it ensures reliable performance in harsh indoor and outdoor environments. With a frequency range of 310–8000 Hz, wide dispersion, and a robust mounting bracket, the HP-30 is ideal for public address, safety, and industrial communication systems.

Technical Dimensions

www.zenitel.com info@zenitel.com Last revision date: 2026-07-16 09:17

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.



Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

GENERAL

Rated power	30 W
SPL 1W / 1 m	110 dB
SPL rated power	124 dB
Effective frequency range	310 - 8000 Hz
Dispersion (-6dB) 1kHz / 4kHz	110° / 32°
Enclosure material / Color	Polyamide / RAL 7035
Mounting material	Plastic bracket
Dimensions	Ø237 x 286D mm
Termination	Spring clamps
Connection	1x M20 cable gland, 1x M20 blanking plug
M20 cable gland sealing range	5 - 12 mm
Weight	1.65 kg
IP-rating	67
Max. / min. ambient temperature	110°C / -50°C
Environmental Condition	Exposed

www.zenitel.com info@zenitel.com Last revision date: 2026-07-16 09:17

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.