DATASHEET

2220010057

BB00224FE

12 port LC Duplex Fibre Optic Patch Panel Singlemode complete



Description

This is innovative, robust 1U sliding patch panel. These panel include an internal mounting plate to install the Adaptors giving a reduction in the bend radius of the exiting patch cords also giving more astatically pleasing installation. With the ability to use a full array of adaptor types offering a flexible solution to the end user, enabling them to incorporate a multi functional panel which allow easy access during installation or re-work with no disturbance of the existing cable or fibres.
In the addition to the array of adaptors the panel also offers multiple cable entry solutions, up to 4 standard cable entry points for loose tube, tight buffer, pre terminated and steel tape armoured cable. Each panels has integrated strength member tie positions also with the additional removable plate at the rear of the panel allows the installation of steel tape armoured cable.

www.zenitel.com info@zenitel.com Last revision date: 2023-05-20 11:47

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

FEATURES

Up to 48 fibres in 1U
Multiple Adaptor options available
24 Adaptor positions - 12 Used
Recessed Adaptor positioning
Individually labelled ports
45° open working angle
Accepts loose tube, distribution and pre terminated cables
RoHS, REACH SvHC and UL rated
Fits standard 19”

SPECIFICATION

Size	1U (44.4mm)
Net weight	2.5 KG
IP rating	IP20
Suitable for Adaptor type	SC Simplex / LC Duplex / E2000
Number of ports	12
Cable Entry 20mm	2
Cable Entry 25mm	2
Mounting Adjustment rang	50mm
Material	Cold- rolled steel
Material thickness	1.2 mm
Material coating	Powder coating
Colour	RAL 9004
Operating temperature	-40°C to +50°C
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754,EN297-1
Compliant to	RoHS, Reach/SVHC

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company’s Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

DIMENSIONS

Height	55 mm
Width	450 mm
Depth	260 mm

www.zenitel.com info@zenitel.com Last revision date: 2023-05-20 11:47

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.