

2220010055

**BC00224FE**

12 port SC patchpanel Singlemode complete with plugs



---

## Description

This is innovative, robust 1U sliding patch panel. These panel include an internal mounting plate to install the Adaptors giving a reduction in the bend radius of the exiting patch cords also giving more astatically pleasing installation. With the ability to use a full array of adaptor types offering a flexible solution to the end user, enabling them to incorporate a multi functional panel which allow easy access during installation or re-work with no disturbance of the existing cable or fibres.

In the addition to the array of adaptors the panel also offers multiple cable entry solutions, up to 4 standard cable entry points for loose tube, tight buffer, pre terminated and steel tape armoured cable. Each panels has integrated strength member tie positions also with the additional removable plate at the rear of the panel allows the installation of steel tape armoured cable.

# Specifications

## FEATURES

---

Up to 48 fibres in 1U

---

Multiple Adaptor options  
available

---

24 Adaptor positions - 12  
Used

---

Recessed Adaptor  
positioning

---

Individually labelled ports

---

45° open working angle

---

Accepts loose tube,  
distribution and pre  
terminated cables

---

RoHS, REACH SvHC and  
UL rated

---

Fits standard 19"

---

## SPECIFICATION

Size	1U (44.4mm)
Net weight	2.5 KG
IP rating	IP20
Suitable for Adaptor type	SC
Number of ports	12
Cable Entry 20mm	2
Cable Entry 25mm	2
Mounting Adjustment rang	50mm
Material	Cold- rolled steel
Material thickness	1.2 mm
Material coating	Powder coating
Colour	RAL 9004
Operating temperature	-40°C to +50°C
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754,EN297-1
Compliant to	RoHS, Reach/SVHC

## DIMENSIONS

Height	55 mm
Width	450 mm
Depth	260 mm