

2220010103

## S03LCM12FEOM4

12 port LC Duplex Fibre Optic Patch Panel Multimode OM4 complete



---

---

### Description

This is innovative, robust 1U sliding patch panel. These panel include an internal mounting plate to install the Adaptors giving a reduction in the bend radius of the exiting patch cords also giving more astatically pleasing installation. With the ability to use a full array of adaptor types offering a flexible solution to the end user, enabling them to incorporate a multi functional panel which allow easy access during installation or re-work with no disturbance of the existing cable or fibres.

In the addition to the array of adaptors the panel also offers multiple cable entry solutions, up to 4 standard cable entry points for loose tube, tight buffer, pre terminated and steel tape armoured cable. Each panels has integrated strength member tie positions also with the additional removable plate at the rear of the panel allows the installation of steel tape armoured cable.

# Specifications

## FEATURES

Up to 48 fibres in 1U

Multiple Adaptor options available

24 Adaptor positions - 12 Used

Recessed Adaptor positioning

Individually labelled ports

45° open working angle

Accepts loose tube, distribution and pre terminated cables

RoHS, REACH SvHC and UL rated

Fits standard 19"

24x Multimode OM4 pigtailed included for 24 duplex connections

## SPECIFICATION

Size 1U (44.4mm)

Net weight 2.5 KG

IP rating IP20

Suitable for Adaptor type LC Duplex

Number of ports 12

Cable Entry 20mm 2

Cable Entry 25mm 2

Mounting Adjustment rang 50mm

Material Cold- rolled steel

Material thickness 1.2 mm

Material coating Powder coating

Colour RAL 9004

Operating temperature -40°C to +50°C

Designed in accordance with TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754,EN297-1

Compliant to RoHS, Reach/SVHC

## DIMENSIONS

Height	55 mm
Width	450 mm
Depth	260 mm