DATASHEET

2220012094

C1000-24FP-4G-L

Cisco C1000 24port 1G PoE+ switch with 4x1G SFP



CISCO Certified

Description

Cisco Catalyst 1000 Series Switches are fixed managed Gigabit Ethernet and Fast Ethernet enterprise-class Layer 2 switches designed for small businesses and branch offices. These are simple, flexible and secure switches ideal for out-of-the-wiring-closet and critical Internet of Things (IoT) deployments. Cisco Catalyst 1000 operate on Cisco IOS Software and support simple device management and network management via a Command-Line Interface (CLI) as well as an on-box web UI. These switches deliver enhanced network security, network reliability, and operational efficiency for small organizations.

IEC60945 Compliant, DNV Type approved for EXIGO and ACM systems by use together with AC filter, 1-phase, 3A, 250VAC

www.zenitel.com info@zenitel.com Last revision date: 2025-10-01 14:47

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

Cisco Catalyst 1000-24FP-4G-L is managed 24-port switch with 24 auto-sensing 10/100/1000 PoE+ ports and 4x Gigabit Ethernet SFP ports .

PORTS	
10/100/1000 RJ45 PoE+	24
SFP	4
Console ports	1x RJ45, USB mini-B and USB-A (for storage and Bluetooth console)

ENVIRONMENT	
Operating temperature	-5°to 50°C
Operating relative humidity	5% to 90% at 40°C (non-condensing)

ELECTRICAL CHARACTERISTICS	
Frequency	50 to 60 Hz
AC voltage	110 to 220 VAC
Current	4.25A to 2.07A
Maximum power Consumption	405.4W
Available PoE Power	370W

DIMENSIONS & WEIGHT	
Dimensions (W x D x H)	445 x 345 x 44 mm
Weight	4.6 kg
Mounting	Rack Mountable, 1HU

Used With

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.



LAN-FLT

AC filter, 1-phase, 3A,
250VAC

Item Number: 2810060003

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.