



2211100150

D81 Messenger

Dect handset

- ✓ IP65 classified design
- ✓ Headset connector and Bluetooth and handsfree.
- ✓ Wide temperature range, -10 to 55°C
- ✓ Loud volume
- ✓ Customizable sounds
- ✓ Color display
- ✓ GAP/CAP compliant DECT handset
- ✓ 18 default languages + 1 customizable
- ✓ Push to talk (PTT)
- ✓ Programmable soft keys / hot keys



Bluetooth

Description

The D81 Messenger possesses advanced alarm and messaging functionality which helps you to communicate with your colleagues smoothly. This handset is a unique combination of robustness and sophistication. A tough design coupled with an outstanding level of functionality and operating safety make it the natural choice for users demanding operational excellence in the most challenging settings, such as industrial plants and secure establishments.

Specifications

GENERAL

Dimensions (L× W × D)	142 × 56 × 25 mm
Weight	175 g (battery and clip included)
Material	Case: PC/ABS, Key pad: PC, Clip: PA
Display (W × H):	28 x 35 mm, Multiple colors with high resolution,
Battery Type	Li-Ion
Battery, Speech Time	18 h (Bluetooth disabled/Location features disabled); 12 h (with Bluetooth headset in use/Location features disabled)
Connector	Multi-purpose: For battery charging, software download, connection of headset, and configuration.
Menu and Message Languages	18 (Czech, Danish, German, Greek, English, Spanish, French, Italian, Magyar, Dutch, Norwegian, Polish, Portuguese (Brazilian), Russian, Slovakian, Finnish, Swedish, Turkish) + 1 customizable
Messaging, Maximum message length	Up to 140 characters from handset, depending on language and system settings.
Messaging, Storage capacity	30 received/sent messages (> 20 000 characters)
Radio. Receiver	

Radio, Receiver sensitivity	-93 dBm
Radio, Automatic DECT protocol detection	Automatic detection and configuration for US DECT and EU DECT at first registration
Radio, Frequency range	1880-1895 MHz (Taiwan); 1880-1900 MHz (Europe, Africa, Middle East, Australia, New Zealand, and parts of Asia); 1900-1906 MHz (Thailand); 1910-1930 MHz (South America); 1920-1930 MHz (North America)
Bluetooth radio spectrum	ISM 2.4000-2.4835 MHz
Operating temperature	-10°C to +55°C
Enclosure protection	IP65
Free fall test	IEC 60068-2-32, procedure 1, dropped 12 times, specification extended to 2 metres; IEC 68-2-32, procedure 2, dropped 1 000 times from 0,5 metre.
Chemical Resistance Test	3% Hydrochloric Acid M-alcohol (85% methylated ethanol) 60% Chlorhexidin 0.5mg/ml
Keypad Abrasion Test	20 NB 0500-B

ACCESSORIES

2211100250	Desktop charger for d81 (EU)
9011702026	Desktop charger for d81 (AU-USA-UK)
9021304000	Belt clip standard for d81 Messenger
2211100253	Charging rack d41/d62/d81/i62/i63
2211100254	Desktop programmer d81/d62/d41
9021304001	Swivel belt clip for d81 Messenger and Protector
9021411000	Leather case for d81
9021411002	Battery pack for d81

HEADSETS

2211200116	Bluetooth Ear piece for DECT handset
2211200117	Bluetooth Headset for DECT handset
2211200001	Headset for DECT d81
9021111000	Headset adapter cable d81 unterminated

Accessories

DISCONTINUED



BTPHR-V2

Bluetooth headset for
DECT handset

Used With



Unite CM Elise3 Std

Elise3 Server Platform



IPBS3-A3

IP DECT base station with
internal antenna