

2211000162

KWS200

IP DECT server Base Station for US, including software license.



- ✔ Supports 12 users and 6 simultaneous calls
- ✔ Delivers high-quality and secure voice communication
- ✔ Supports DECT Enhanced Security (Encryption)
- ✔ Enhance coverage via repeaters

Description

KWS200 Server is an enterprise grade single-cell IP-DECT solution that can grow with your business, providing mobility for users within specific areas of any office environment.

Product frequency band:

- ✔ USA & Canada :1920–1930MHz (DECT6.0)
- ✔ South America: 1910–1930MHz

Note: 2211000162 includes item 2211000160 (IP DECT Server KWS200) and 2211000161 (Software Assurance License for 1 year)

Specifications

GENERAL

Size	100 x 100 x 43 mm (3.94 x 3.94 x 1.69 in.)
Weight	Weight: 120 gr. (4.2 oz)
Codecs	G.711 A-law and U-law, G.726 (32 kbps - 4 bit ADPCM), G.729
Electrical Requirements	PoE
Typical range	Indoor: 20 - 50 m, Outdoor: 300 m.
Frequency Range	USA, Canada:1920– 1930MHz (DECT6.0); South America: 1910– 1930MHz

Used With



7212 DECT Handset
1G9

DECT Handset, IP54.
Frequency US



7642 DECT Handset

DECT Handset with
Bluetooth, IP64