zenitel

DATASHEET



2310131027

OCABLMPXARM4

Armoured multicable with barrier gland 4m for MVX-MPX

- Pre-cabled for Ethernet, video, I/O and telemetry connections
- Equipped with barrier cable gland
- Resistant to oil, flames and ultra-violet rays
- Designed for potentially explosive zones
- 4 meter version

Description

Armoured multicable for explosion-proof Pan & Tilt of the MAXIMUS MPX/MPXT/MPXHD series
The pre-assembled cables simplify product installation.
Suitable for use in hostile environments, available in 4meter length.

Technical Dimensions

www.zenitel.com info@zenitel.com Last revision date: 2024-05-06 12:26

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

TECHNICAL DRAWINGS

The indicated measurements are expressed in millimetres.



VIEW OF CABLE SECTION (0CABLMPXARM)

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

Specifications

GENERAL	
Armoured, multi-polar, assembled, black cable with barrier cable gland 3/4" NPT	
Cabling for Pan & Tilt MAXIMUS MPX/ MAXIMUS MPX DELUX: 1 Ethernet cable, 3 power supply conductors, 1 coaxial video cable, 7 conductors for alarms, relay and telemetry	

MECHANICAL	
Armoured cable	
Length: 4m (13.1ft)	
External diameter: 20.0mm (0.78in) ± 0.5mm (0.02in)	
Minimum bending radius: 220mm (8.6in)	

ELECTRICAL	
Power supply	• Number of conductors (electrical): 3
	• Section: 2.5mm²
	• Working voltage: 300V max

NETWORK	
Ethernet: 1 cable, Category 5E, shielded cable	

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.

SERIAL COMMUNICATIONS

Telemetry: RS-485
(MAXIMUS MPX only)

Remote resetting: for
MAXIMUS MPXHD only

VIDEO

1 coaxial cable, RG179

I/O INTERFACE

Alarms: 1 for MAXIMUS
MPX DELUX, 2 for
MAXIMUS MPX

Relay: 1

ENVIRONMENT

Temperature: from -60°C (-
76°F) up to +80°C (+176°F)

Type of laying: fixed
installation

Oil resistant (complies with
CNOMO E.03.40.150N,
ASTM n.2, IRM 902, VDE
0472 p.803 test B)

UV resistant (complies with
ICE60068-2-5)

Flame resistant (complies
with IEC/EN60332-1,
IEC/EN60332-3-22)

CERTIFICATIONS

IEC/EN 60079-14 (ATEX
Ex II)

IP protection degree: IP66
(cable gland only)

Used With

www.zenitel.com info@zenitel.com Last revision date: 2024-05-06 12:26

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.



MPXHD21A000C Series2 EX PTZ Camera

MPX Series 2 Delux IP PTZ Ex camera, super low-light, full HD

Item Number: 2310131030

www.zenitel.com info@zenitel.com Last revision date: 2024-05-06 12:26

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend; Zenitel – All rights reserved.