


2970000053

## UPS-XPC-2700-120R

Rack mount online UPS, 2700W/30 min, 120V, wo/ rails



- ✓ Auto restart
- ✓ 99% efficient operation
- ✓ Smart LCD display
- ✓ Programmable receptacle group
- ✓ Temperature compensation
- ✓ Hot swappable battery
- ✓ Extended battery runtimes
- ✓ Maintenance bypass
- ✓ 6HU
- ✓ Minimum cabinet depth: 800mm

## Description

The P80 is a true online UPS that delivers continuous, high quality AC power to servers and network equipment with no break when transferring to battery. The P80 offers the lowest total cost of ownership by cutting energy costs and lowering heat output.





- ✓ Available models: P80-1500, 2200, 3000
- ✓ Pure sine wave output
- ✓ Extended battery runtimes with optional matching battery modules
- ✓ UL, cUL, RoHS

Item 2970000133, consists of:

- ✓ UPS P80-3000, 3000VA/2700W 120V (2U)
- ✓ Two Extended Battery packs P90-BP72(2U)

*\*Note: Rails not included. Two Rail kits (2970000130) needed for P80-1500, P80-2200, P80-3000*

## Technical Dimensions



# Specifications

## GENERAL

Power rating	3000VA (2700W)
Input Voltage Nominal/Frequency	120VAC; 50/60Hz auto-sensing
Output Voltage	120VAC nominal (110/115/127 selectable)
Harmonic distortion	2% @ 100% linear load; 5% @ 100% non-linear load
Efficiency	Up to 99% ECO mode, 95% buck and boost mode
UPS, Dimensions (W x D x H)	17.2 x 23.6 x 3.5 in
UPS, Weight	67.1 lbs
Battery Type (included)	Up to 30 minutes
Battery, Dimensions (W x D x H)	17.2 x 23.6 x 3.5 in
Battery, Weight	104.4 lbs

## ACCESSORIES

2970000130	4-Post Rail Kit for use with P80-1500, P80-2200, P80-3000
------------	--

## Accessories



### UPS-XPC-CARD

Dry Contact Interface Card